

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 046020

PRIMARY CORNER DESCRIPTION NW Cor. Alexander Dumond DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC survey by J.A. Burnett, dated June 8, 1857 - (DCSO records, DLC volume Page 609)

Set a post, from which
A Laurel 12" dia., bears S.25°W., 20 lks.
A Laurel 14" dia., bears N.20°E., 19 lks.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume Page 708)

The post, set for this cor. is gone, but both bearing trees are standing. I restore this corner by setting a Cedar post 4½ ft. long, 4" sq., 24" in the ground marked T30S R4W C. 46 on SE. face, from which
A Laurel 16" dia., bears N.20°E., 19 lks. dist. mkd. T30S R4W C.46 BT.
A Laurel 14" dia., bears S.25°W., 20 lks. dist. mkd. T30S R4W C.46 BT.
These are the original bearing trees, whose marks being dim, I renew.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-91

Found - 2½" I.Pipe, 3.5 ft. above surface. (No record source, probably Wenderoth's)
Orig. 12" now down, 24" Laurel, S.25°W., 13.2 ft., open and found scribing.
Orig. 14" now 30" Laurel, N.20°E., 12.5 ft., shows scar.
New BTs -12" R.Fir bears S.70°W., 23.8 ft. scribed Cl. NW 46 CS BT.
10" W.Fir bears South, 3.7 ft., scribed Cl NW 46 CS BT.