

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 047010

PRIMARY CORNER DESCRIPTION NE Cor. George T. Day DLC #47

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC Vol. Page 611)

-----  
Set a post marked, from which  
A B.Oak 24" dia., bears S.35°W., 102 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Vol. Page 713)

-----  
A Post is standing in place but not the original, the bearing tree is also standing. The post being partly decayed, I restore this corner by setting a Laurel post, 4½ ft. long, 4" sq., 24" in the ground, marked T30S R4W C.47 on SW. face, from which the original tree:  
A B.Oak 30" dia., bears S.35°W., 102 lks. dist. mkd. T30S R4W C.47 BT.

G. G. Stewart - Wit: H.A. Hill and W.S. Crear - April 6, 1922 - C.S. File 7/6

-----  
Set seasoned Oak post from stump hole of O.B.T.  
Marked:  
A 24" B.Oak S.48°E., 17.8 ft.  
A 12" Laurel S.65°W., 38.0 ft.

Douglas Co. Surveyors Office - John M. Powell and J. Heritage, crew - Feb. 17, 1972 - C.S. File 53/26-51

-----  
Found - 24" Oak S.48°E., 17.8 ft., scribe visible "C47 CS" on old burnt face.  
5/8" Iron rod at DLC corner. (No record)  
20" D.Fir S.87°W., 22.4 ft. (No record)  
22" Cedar N.44°E., 34.2 ft. (No record)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23513-4)

-----  
The NE cor. of DLC No. 47, perpetuated by the Douglas County Surveyor's Office in 1922, from original evidence no longer in existence, further perpetuated by person(s) unknown as reported by the Douglas County Surveyor's Office in 1972, monumented with an iron rod, 5/8" dia., 26" long, firmly set, projecting 6" above ground, from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1922  
A root hole bears S.57½°E., 17.4 ft., with fallen black oak trunk, 25" dia., lying alongside, with no marks visible.  
continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 047010

PRIMARY CORNER DESCRIPTION NE Cor. George T. Day DLC #47

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A madrone, 20" dia., bears S. 64 $\frac{3}{4}$ °W., 37.1 ft., with a healed blaze.

and bearing trees mkd. by person(s) unknown, reported by the Douglas County Surveyor's Office in 1972

A cedar, 30" dia., bears N.40 $\frac{3}{4}$ °E., 34.3 ft., with a healed blaze.

A fir, 32" dia., bears S.82°W., 22.5 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T 30 S R 4 W

S 3

DLC 47

2015