

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 047020

PRIMARY CORNER DESCRIPTION NW Cor. George T. Day DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, Page 610

Set post marked a quadrangle trench and stone in the center.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume Page 713)

The old post is gone, and cultivation has obliterated all traces, on the ground. I am due South of NE. Cor. of Claim No. 46 and on line with the SW. cor. of this claim. I restore this cor. by setting Fir post 4½ ft. long, 4" sq., 24" in the ground, marked T30S R4W C.47 on the SE. face.

G.G. Stewart, Deputy Co. Surveyor - Wit: W.S. Crear and H.A. Hill - April 7, 1922 - C.S. File 7/6 and Field book 3 Pg. 12

Reestablished by running needle line, West, sun bearing, from point 137.3 ft. North of section cor. 3, 4, 9 and 10, as set, 1559.0 ft. as per field notes by Claim survey. No corner could be found. Set Iron pipe marker and marked:
A 24" Cedar N.1°W., 74.6 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-90

Found - 1/2" I.P. at corner, flush.
24", now down 36" Cedar N.1°W., 74.6 ft., shows scar
New BTs -6" Cedar bears N.81°E., 19.9 ft. scribed NW C147 CS BT.
5" Cedar bears S.32°E., 35.8 ft. scribed NW C1 47 CS BT.
(Corner lies 5.0 ft. from the west fence of two fences running parallel North and South, 24 ft. apart)

Fd. OK, June 1970 by Larry Bishop - M 42-1

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23514-15)

The NW cor. of DLC No. 47, reestablished by the Douglas County Surveyor's Office in 1922; there is no remaining evidence of the original cor., therefore this position is accepted as the cor., monumented with an iron rod, 5/8" dia., 32" long, firmly set, flush with the ground.
At the corner point
continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 047020

PRIMARY CORNER DESCRIPTION NW Cor. George T. Day DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28" long, 2½" dia., flush with the ground, directly over the iron rod, with brass cap mkd.

T30S R4W

S4

|DLC 47

2015

from which

An iron rod, 30" long, 5/8" dia., driven flush with the ground for a reference monument, bears S.45°08'39" W., 5.63 ft., with aluminum cap mkd. RM NW COR DLC 47 5.6 FT TO COR 2015, and an arrow pointing to the cor.

An iron rod, 30" long, 5/8" dia., driven flush with the ground for a reference monument, bears N.45°12'36"W., 6.00 ft., with aluminum cap mkd. RM NW COR DLC 47 6.0 FT TO COR 2015, and an arrow pointing to the cor.