

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume Page 611)

Cor. on edge of river, from which
A W.Oak 20" dia., bears N.88°E., 438 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume, Pages 711-12)

As the true corner is in the river, at a point 3.30 chs. East of true corner, I set a basalt stone 24 x 8 x 4" marked 47 W.C. on NE. face in a mound of stone, from which

A Laurel 9" dia., bears S.70½°E., 33 lks. dist. mkd. T30S R4W C.47 W.C. BT.

A Pine 12" dia., bears N.40 3/4°E., 30 lks. dist. mkd. T30S R4W C.47 W.C. BT.

The old post, set for this cor. is gone, also the bearing tree: but the line tree described in the field notes, namely a B.Oak 14" dia. is standing, marked with 2 notches on E. and W. sides, which enabled me to find the true line.

G.G. Stewart, Deputy Co. Surveyor - Wit: Montgomery, Morgan, Moore and Beals - M 2-9; Vol. 3 Pg. 136; C.S. File 7/31

Found one original BT and stump of other. Together with rock for corner. Marked:

An 8" Fir S.12°E., 18.9 ft.

An 18" Laurel (?), 21.7 ft. (O.B.T.)

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey and Mike Stone, crew - Aug/Sept. 1963 - C.S. File 53/26-104

Found - 6" x 8" stone, 12" above ground with chiseled + on top.

Now 24" Laurel that shows part of old face and good scar below, S.70°E., 21.8 ft.

No trace of Fir to SE.

Corner near top of river bank and 6 ft. North of old fence line.

New BT - 16" R.Fir bears S.56°E., 48.5 ft. scribed WC SSW DLC 47 CS BT.

Rescribe-24" Laurel S.70°E., 21.5 ft. WC DLC 47 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION WC S SW Cor. Geo T Day DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by William Ruppert, LS #866 - For: Don Phillips -
Sept. 1984 - C.S. File 58/215

Found - 22" D.Fir, good scar, and BLM BT tag.
Set 1" x 30" Iron pipe with 2½" brass cap, N.56°W., 48.5 ft.
from bearing tree. Brass cap mkd. T 30 S

WC ←
| 217.8
----DLC47
R4W
LS 866
1984

Set a 5/8" x 30" Iron rod with a 3/4" brass washer marked
LS866, N.79°07'E., 26.81 ft. as a reference.

Fd. OK by D. Beedle, Sept. 2003 - see part. plat 2003-0074

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Mike
Koch - 8/9/2016 (filed 3/17/2020) - C.S. File 67/46-21

Found - A 1" dia. i.d. iron pipe by Ruppert, plumb and firmly
set, projecting 12" above a 3 ft dia. stone collar
with a 2½" dia. brass cap (properly) mkd

A BT by Byron, in 1963 -

A 31" dia. D.Fir bears S.56°E., 48.5 ft. with a
healed blaze.

A BO by Ruppert in 1984 -

A 5/8" diam. iron rod projecting 4" above the ground
bears N.79°E., 26.8 ft (Rec N.79°07'E., 26.81 ft)

New BTs- A 12" dia. P.Pine bears S.70°E., 16.5 ft. scribed
"WC SSW DLC 47" "CS BT" . A 24" diam. P. pine
bears N.4½°W., 24.6 ft. scribed "WC SSW DLC 47
CS" "BT".

Note - All bearing trees have BT Tags attached. All new
bearing trees have double blazed faces with
bearing measured to the center of the trees at
the root crown and distances measured to the side
and center of the root crown.

The corner falls on a gentle slope on the east shore
of the South Umpqua River near the mean high
water line.

Compass decl. 15°E.