

PRIMARY CORNER DESCRIPTION NE Cor. Andrew Thomas DLC #48

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, Page 612)  
 -----  
 Set a stake marked a quadrangle trench and stone in center. Thomas house bears S.40°W., 12.00 chs.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume, Page 715)  
 -----  
 Intersect sec. line between secs. 3 and 10, 23.30 chs. East of ¼ sec. cor. Here I found a basalt rock 6 x 8 ins., well buried in the ground. I am informed that this has been put in the place of original post and is considered correct. I find the same to be in true line between the NW. cor. of Claim 49 and SE. cor. of Claim 48 and E and W; I mark the top of the same "48". and dig pit, 24 x 24 x 12 ins. and raised a mound along side.

J.W. Cole - March 4, 1924 - Field Book 52 page 58 and Vol. 3 Pg. 186  
 -----  
 (FB 52 Pg. 58)  
 I made diligent search with shovel and sounding rod for the NE. Cor. of Claim 48, hunting an area 4 ft. wide for 40 ft. down hill from pipe and stake noted by Frear. (Vol. 3 Pg. 186)  
 Went to an iron pipe at the North East corner of DLC No. 48 which I accepted as the corner having no better evidence of its original position.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16819-20)  
 -----  
 Point for the NE. cor. of Donation Land Claim No. 48 at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.  

T 30 S R 4 W	
— S 3	C 49
C 48	
1981	

from which  
 An Iron post 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.11°W., 9½ lks. dist., with brass cap mkd. C48 RM 1981 and an arrow pointing to the corner. (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 048010

PRIMARY CORNER DESCRIPTION NE Cor. Andrew Thomas DLC #48

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>An iron post 28" long, 2½" dia., set 24" in the ground, for a reference monument bears N.10°W., 8½ lks. dist., with brass cap mkd. T30S R4W S3 RM 1981 and an arrow pointing to the corner.</p>
<p>Found OK by N. Hibbs, May 2003 - M137-63</p>
<p>BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23515-6)</p> <p>-----</p> <p>The NE cor. of DLC No. 48, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. from which accessories mkd. by Jelley in 1981-82</p> <p>An iron post, 2½" dia., projecting 4" above ground, bears S.9°49'26"W., 5.98 ft., with brass cap mkd. C48 RM 1981, and an arrow pointing to the cor. (Record, S.11°W., 6.27 ft.)</p> <p>An iron post, 2½" dia., projecting 4" above ground, bears N.9°34'21"W., 5.66 ft., with brass cap mkd. T30S R4W S3 RM 1981, and an arrow pointing to the cor. (Record, N.10°W., 5.61 ft.)</p>