

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 048040

PRIMARY CORNER DESCRIPTION S SE DLC Cor. Andrew Thomas DLC #48

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, Page 613)

-----  
Set a post marked, from which  
A W.Oak 5" dia., bears N.18°W., 27 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume Page 714)

-----  
Found a post without marks, in place, replace and restore cor. by setting a Fir post 4½ ft. long, 4" sq., 24" in the ground, mkd. T30S R4W C.48 on NW. face, from which  
A B.Oak 12" dia., bears S.70°W., 46 lks. dist. mkd. T30S R4W C.48 BT.  
A W.Oak 7" dia., bears N.18°W., 27 lks. dist. mkd. T30S R4W C.48 BT. This is the original bearing tree, whose marks being dim, I renew.

G.J. Wenderoth, Deputy Co. Surveyor - Nov. 1945 (Record Source not found, old Renewal #68)

-----  
Renewed by chaining North and West. Set ¾" Iron pipe, marked  
8" W.Oak N.3°30'W., 46.2 ft.  
10" Fir S.68°30'W., 24.3 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-88

-----  
Found - 1" I.P. at corner and both BTs as recorded by Wenderoth in 1945.  
SW. BT, now dead, partly.  
8" W.Oak N.3°W., 46.2 ft., is OK.  
New BT - 7" R.Fir bears N.68°W., 20.3 ft. scribed SE DLC 48 CS BT.  
N-S fence 10 ft. West.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/3/1999 - C.S. File 66/8-21

-----  
Found - 1" i.d. iron pipe, protrudes 4" above ground.1945  
8" now 10" dia., W.Oak with a fully healed double blaze bears N.4½°W., 46.2 ft. (rec. N.3½°W., 46.2 ft.) 1945 (this tree is dead will be cut down in near future)  
10" now 24" dia. D.Fir with a fully healed double blaze bears S.68½°W., 24.3 ft., this tree is alive and healthy. 1945 -- continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 048040

PRIMARY CORNER DESCRIPTION S SE DLC Cor. Andrew Thomas DLC #48

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

7" now rotted to ground D.Fir, bears N.68°W., 20.3 ft. 1963  
Set - 2 3/8" dia. brass cap on a 1 3/8" by 32" long iron pipe is set at position of found iron pipe, protrudes 6" above ground. Stamped:  
DOUGLAS COUNTY SURVEYORS  
T30S  
DLC | R  
48 | 4  
1999 W  
OFFICE  
Fd. IP measured 33" long is set along S edge of BC/IP, protrudes 4" above ground.  
19" dia. D.Fir double blazed and scribed "SSE DLC 48 CS BT" bears N.31½°W., 28.3 ft.  
12" dia. D.Fir double blazed and scribed "SSE DLC 48 CS BT" bears S.42½°E., 23.2 ft.  
8" D.Fir double blazed and scribed "SSE DLC 48 CS BT" bears N.55½°E., 22.9 ft.  
Corner lies at the intersection of an E-W and N fence lines.