

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, page 613)  
-----  
Set post marked, from which  
    A W.Oak 20" dia., bears S.5°W., 68 lks. dist.

---

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume, Page 714)  
-----  
Interior angle cor. Here I found a basalt stone 15 x 10 x 6 ins. in place, also the bearing tree for this cor. I marked said stone 48 on its NW. face, from which  
    A W.Oak 27" dia., bears S.5°W., 68 lks. dist. mkd. T30S R4W C.48 BT. This is the old bearing tree, whose marks I renew.

---

G.J. Wenderoth, Deputy Co. Surveyor - Nov. 1945 - (No record source found, information from old renewal #67)  
-----  
Renewed from orig. BT. Set 1/2" Iron pipe.  
    20" W.Oak S.5°W., 44.88 ft.

---

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey and Mike Stone, crew - Aug/Sept. 1963 - C.S. File 53/26-96  
-----  
Found - 1/2" Iron pipe at South shoulder of county road. and 8" below surface.  
    Now 32" W.Oak, S.5°W., 44.9 ft., shows scribing.  
    20" Pine bears S.42°E., 21.1 ft., shows good scribing. (This BT not of record)  
Set 3/4" Iron rod alongside corner pipe and 1" below surface.

---

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/2/1999 - C.S. File 66/8-18  
-----  
Found - 3/4" I.R. is fd. 6" below gravel road shoulder 1963  
    20" now 32" dia. W.Oak with a previously opened blaze, no scribing visible, bears S.5°W., 44.9 ft. [agrees with rec.] OBT  
    20" now 24" dia. Pine w/fully healed blaze, bears S.42°E., 21.1 ft. [agrees w/rec.]. Rec'd in 1963  
Set: 28" dia. W.Oak double blazed and scribed "INT SE DLC 48 CS BT" bears N82 1/2°W, 101.4 ft.  
    5/8" iron rod protrudes 3" above ground, bears N.48 1/2°E., 166.7 ft.  
Corner lies 4 ft. southerly of edge of pavement.