TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049030

PRIMARY CORNER DESCRIPTION Int. L. F.O. Worley DLC 49

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, Page 614

Set a post marked, from which
A B.Oak, 20" dia., bears N.51°E., 46 lks.

GLO survey by Wm Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume, Pgs 717-18)

Interior angle corner; the post set for this cor. is gone, but the BT stands. I restore this cor. by setting a cedar post 4½ ft. long, 4" sq., 24" in the ground, marked T30S R4W C 49 on SE face, from which
A B.Oak 32" in dia., bears N.51°E., 46 lks., marked T30S R4W C49 BT. This is the old BT, whose marks being dim, I renew.

Neil Hibbs - For: Douglas Wagner - May 2003 - M 137-63

Set - 5/8" x 30" iron rod w/cap stamped "HIBBS-LS52989", set at record bearing & distance from fd. 42" Oak stump.
42" Oak stump bears N.51°E., 46 lks., (30.36')
14" Ash bears S.29½°E., 224.9' (Westerly trunk of double tree)
14" Apple bears S.67½°W., 272.6'