

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049040

PRIMARY CORNER DESCRIPTION W NW Cor Franklin 0 Worley DLC 49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, page 614)

-----  
Set a post marked, from which  
A B.Oak 14" dia., bears S.67°E., 32 lks.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume, Pg. 717)

-----  
I found here a post, marked T30S R4W C.49, lying down; but the bearing tree is standing. I restore the cor. by setting a Laurel post 4½ ft. long, 4" sq., 24" in the ground, marked T30S R4W C.49 on SE. face, from which  
A B.Oak 18" dia., bears S.67°E., 32 lks. dist. mkd. T30S R4W C.49 BT. This is the old bearing tree, whose dim marks, I renew.

J.W. Cole - Wit: L.H. Billings; J. Sutton; J.R. Chaney; P.L. Beals - March 1924 - Field book 52 Pg. 58; Vol. 3 Pg. 186

-----  
I found an old stake properly marked but which did not exactly correspond with calls of the bearing tree. I set the corner to correspond to the calls on the original BT which was standing. The scars having been cut open were rotted out. I marked new trees:  
A B.Oak 18" dia., S.10°E., 16.5 ft.  
A Fir 12" dia., S.65°W., 6.5 ft.  
I set a galv. Iron pipe 1½" dia., 40" long, 36" in the ground at corner.

Douglas Co. Surveyors Office - J.W. Byron; Ray Irving; John Fee, crew - May 14, 1954 - C.S. File 46/45-2 (pgs 2-3)

-----  
Found - 1½" Iron pipe at corner, checks bearing and distance to 18" R.Fir, S.65°W., 6.5 ft., scribing visible, fair condition.  
B.Oak BT down and rotted.  
Blazed and scribed:  
6" R.Fir S.77°W., 19.2 ft. mkd. NW CL. 49 CS BT.  
10" Cedar N.44°E., 23.6 ft. mkd. NW CL 49 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-100

-----  
Found - All BTs as recorded.  
10" now 14" Cedar N.44°E., 23.6 ft., shows scribing.  
8" Fir S.77°W., 19.2 ft., shows scribing.  
(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049040

PRIMARY CORNER DESCRIPTION W NW Cor. F.O. Worley DLC #49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>18" Fir stump S.65°W., 6.5 ft., shows scar. Corner pipe not found. Set brass cap at cor. mkd: County Surveyors Office NW DLC 49 T30S R4W 1963</p>
<p>BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16820)</p> <p>-----</p> <p>(Corner report only) The NW. cor. of DLC #49, perpetuated and recorded by Cole in 1924, from original evidence no longer in existence, and further perpetuated and recorded by Byron in 1954 and 1963, monumented with an iron post 1¼" dia., firmly set, projecting 6" above ground, with 1963 brass cap from which the remains of a bearing tree mkd. by Cole: A sawed Fir stump 20" dia., bears S.61°W., 9½ lks. dist. with healed blaze. A Fir 13" dia., bears S.74°W., 30 lks. dist. with healed blaze.</p>
<p>Found OK by N. Hibbs, May 2003 - M137-63</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause &amp; Mike Koch - 2/14/2017 (filed 11/7/2022) - C.S. File 67/54-49</p> <p>-----</p> <p>Found - From the 1963 DCSO renewal a 2½" dia., brass cap on a 1" I.D. iron pipe set plumb, protruding 18" above ground. The brass cap is (properly) marked. No evidence remains of OBT Evidence of Two 1924 Cole renewal BTs A B.Oak 18" dia., now a root depression, with rotted Oak remains nearby, downhill; bears S.10°E., 16.5 ft. (as per record) A Fir 12" dia., now 18" dia., 2½ ft tall D.Fir stump with a previously opened and now re-healed single blaze; S.65°W., 6.5 ft. (as per record) Two 1954 DCSO renewal BTs A 10" Cedar now a 31" dia., I.Cedar with a fully healed double blaze; bears N.42½°E., 23.6 ft. (rec. N.44°E., 23.6 ft) A 6" R.Fir now a 19" dia., D.Fir with a fully healed double blaze; bears S.77°W., 19.2 ft (as per rec) New - A 14" dia., D.Fir scribed "NW DLC 49 CS BT" on a double blaze; bears S.61¼°E., 20.5 ft. CONT.</p>

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049040

PRIMARY CORNER DESCRIPTION W NW Cor. Franklin 0 Worley DLC 49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - A 13" dia., D.Fir scribed "NW DLC 49" "CSBT" on a double blaze; bears N.2°W., 27.7 ft.  
Compass decl. 15°E.  
Corner monument is on a moderate SE slope in an old select cut forest of Fir, Ced., Mad., Oak, pine, maple.