

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049050

PRIMARY CORNER DESCRIPTION SW Cor. E.O. Worley DLC #49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey Volume, Page 614)

-----  
Set a post marked, from which  
A W.Oak 12" dia., bears S.65°E., 104 lks.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Volume Page 717)

-----  
I found here a basalt stone 8 x 7 ins. sq., 4" above ground, well buried, marked the same for corner 49. on top face, from which  
A W.Oak 20" dia., bears N.65°E., 104 lks. dist. mkd. T30S R4W C.49 BT. This is the old bearing tree, whose marks, being dim, I renew.

O.F. Thiel - For: Chaney - Nov. 14, 1913 (recorded 8/1998) - F.B. 115 Pg 96

-----  
Set a quartz stone 12x8x4 a little W. of center of Co. road by a W.Oak, 30" bears N.65°E., 1.04.

J.W. Cole - Wit: L.H. Billings; J. Sutton; J.R. Chaney; P.L. Beals - March 1924 - Field book 52 Pg. 58; Vol. 3 Pg. 34; Vol. 3 Page 186

-----  
I renewed this corner from a W.Oak BT, which I chopped open and found the scribe marks. I ran S.W. 104 lks. and dug over wide area in search of marked rock. This could not be found. I set a blue river boulder, 5" x 7" x 12", shaped like a flat iron on top and marked with X, 12" below surface of ground. I marked new BT:  
A double W.Oak 12" dia., S.69°W., 15.2 ft.

Douglas Co. Surveyors Office - J.W. Byron; Ray Irving; John Fee, crew - May 14, 1954 - C.S. File 46/45-2 (pg 6)

-----  
Bearing tree set by Cole in 1924 removed by road crew and 4 ft. of fill over corner. We chopped out a 4 ft. W.Oak, checks for original BT except bearing should be N.65°E. No scribing visible as center is rotted. We set temp. corner using said tree. Then made survey as shown in notes, which checks for position of temp. corner.  
Set 1" Bolt with 1 3/4" Hex head flush with surface of oil material. Blazed and scribed:  
5" W.Oak S.88°W., 24.3 ft. mkd. T30S R4W SW Cl. 49 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 049050

PRIMARY CORNER DESCRIPTION SW Cor. E.O. Worley DLC #49

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Gregory Quibell, Deputy -  
Teresa Buley, witness - Nov. 3, 1981 - C.S. File 61/24-9

-----  
Found - 1" bolt with 1 3/4" hex head flush with pavement  
lying partially on its side.  
5" now 8 1/2" down partially rotten Oak with BT tag.  
Face and scribing not visible because of  
condition of tree. Stump hole of BT bears  
N.88°E., 24.3 ft. (Rec. calls for S.88°W., but  
this falls in road.)  
Fence corner with yellow tag bears N.80°E., 18.2 ft.  
Fence runs North, South and East.  
New BTs -42" W.Oak bears N.32°E., 87.3 ft. scribed SW CL 49  
CS BT in double blaze.  
5" W.Oak bears S.63°E., 18.6 ft. scribed SW CL 49 CS  
BT in double blaze. Township and range were not  
scribed in order to keep size of blaze smaller,  
a land owners request. 5" Oak BT is in R/W fence.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under  
Group #1070, surveyed June 1981/May 1982 - (DCSO records  
Vol. 43 Page(s) 16819)

-----  
The SW. cor., perpetuated by Cole in 1924, from original  
evidence no longer in existence, and further perpetuated and  
recorded by Byron in 1954, and still further perpetuated and  
recorded by Quibell in 1981, monumented with an iron bolt, 1"  
dia., firmly set flush with asphalt surface of county road,  
from which the remains of a bearing tree mkd. by Byron:

A root hole bears N.88°E., 37 lks., with a down Oak  
alongside, 8" dia., no marks visible.  
and bearing trees mkd. by Quibell:

A W.Oak 42" dia., bears N.30 3/4°E., 133 lks., with scribe  
marks SW CL 49 CS BT visible on open double blaze.

A W.Oak 5" dia., bears S.64°E., 28 1/2 lks. with scribe marks  
SW CL 49 CS BT visible on open blaze.

and reference monuments:

An Iron post 28" long, 2 1/2" dia., set 24" in the ground for  
a reference monument, bears N.53 1/4°E., 35 lks. with  
brass cap mkd. C 49 RM 1981 and an arrow pointing to  
the corner.

An Iron post 28" long, 2 1/2" dia., set 24" in the ground,  
for a reference monument, bears S.44°E., 34 lks. dist.,  
with brass cap mkd. T30S R4W S10 1981 and an arrow  
pointing to the corner.

Corner is located on E. edge of Days Creek Road, 30 lks.  
wide, bears N.5°E. and S.15°W. (continued next page)

