

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 and 12 only, T30-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7166)

Intersect E. bdy. of Township, 303 lks. South of cor. of secs. 1, 6, 7 and 12.

I set a Fir post, 3 ft. long 4" sq. 24" in the ground, for closing corners of secs. 1 and 12, marked: CC T30S R5W on W., S1 on N., and S12 on S. faces; with 1 groove on N., and 5 grooves on S. faces, from which

A Laurel 7" dia., bears S.22°W., 35 lks. mkd. T30S R5W S12 BT.

A Laurel 6", bears N.35°W., 45 lks. mkd. T30S R5W S1 BT. As these trees are easily killed by fire and no other in limits, I added:

A Pine 40" dia., bears N.66½°E., 53 lks. dist. mkd. T30S R5W CC S1 and 12 BT.

All marks relating to secs. 1 and 12 were destroyed on the old post and bearing trees.

A.R. Evans, Deputy Co. Surveyor - July/Aug. 1951 - C.S. File 45/69

Set a 5/8" Iron rod from 2 original bearing trees:

7" Laurel (dead), S.22°W., 35 lks.

40" Pine N.66½°E., 53 lks.

Blazed and scribed new BTs

20" Fir N.58°W., 25.4 ft. mkd. T30S R5W CC S1 CS BT.

14" Fir S.39½°W., 25.2 ft. mkd. T30S R5W CC S12 CS BT.

BLM resurvey by Roseberry and Jelley, under Group #662 - Surveyed, Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15509-10)

Found closing corner perpetuated and recorded by A.R.Evans in 1951, monumented with an iron rod, 5/8" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:

A Pine 33" dia., bears N.63½°E., 53 lks. dist., with scribe marks T30S R5W CC visible on partially healed double blaze. (Rec. N.66½°E.)

A Madrone snag 7" dia., bears S.29½°W., 35 lks. dist, with scribe marks 30S R5W S12 BT visible on partially healed double blaze. (Rec. S.22°W.)

and bearing trees marked by Evans

A Fir 15" dia., bears S.41°W., 39 lks. dist., with scribe marks T30S R5W CC S12 CS BT visible on bark blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 100577

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 and 12 only, T30-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 23" dia., bears N.58 3/4°W., 42½ lks. dist., with scribe marks T30S R5W CC S1 CS BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd:

T 30 S		T 30 S	
CC	S 1		S 7 R 4 W
	S 12		
	R 5 W		
			1969

DCSO-GIS Corner visitation - 3/9/2004 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 2½" IP/BC