

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 113700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only, T29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6357)

Set ¼ sec. post at proper distance, from which
A Laurel 5" dia., bears N.18°W., 35 lks. dist.
A Laurel 6" dia., bears S.45°W., 27 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 15 Page(s) 6408)

The locality of the ¼ sec. corner has been burnt over, destroying all traces.
Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 48" dia., bears N.32°W., 19 lks. dist. mkd. ¼ S BT.
A Maple 8" dia., bears N.36°E., 74 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - Wit: George Vaughn; Dennis Vaughn - ~~Aug. 17, 1951~~ 7/18/1951 - C.S. File ~~40/375~~ 40/304-2

Determined by O.B.T., a Fir 52" dia., bears N.32°W., 12.5 ft., scribe showing.
At corner point, Set 1" x 30" Iron pipe, from which
A Cedar 10" dia., bears N.1°E., 30.0 ft. mkd. ¼ S S31 BT
A Maple 10" dia., bears N.80°W., 62.0 ft. mkd. ¼ S 2880 BT
Tsp. corner bears S.76½°W., 700.0 ft.
N. 1/4 Corner Sec. 6, T30-4, bears N.76°30'E., 2076.0 ft.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19770-1)

From the ¼ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., perpetuated by Markham, in 1951, monumented with rust lined hole, 1¼" diam., with an iron pipe, 1¼" diam., 24" long, lying alongside, from which the remaining original BT:
A fir, 56" diam., bears N.32°W., 19 lks. no marks visible. and a bearing tree mkd. by Markham
A maple, 17" diam., bears N.80¼°W., 89 lks., with fragmentary scribe marks visible on opened blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T29S R4W
¼ S 31
1992
from which a new bearing tree
A fir, 6" diam., bears N.3½°E., 77½ lks., mkd 1/4 S31 BT.