

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Orig. GLO survey by Nathaniel Ford, Deputy Surveyor, under contract No. 44 dated May 30th, 1854 - (DCSO records Vol. 16 Page(s) 6985)</p> <p>-----</p> <p>Set ¼ Sec. post at proper distance; from which A laurel, 6" dia., bears N.55°E., 6 lks. A laurel, 6" dia., bears S.5°W., 12 lks.</p>
<p>Original - Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Pages 7023)</p> <p>-----</p> <p>Set a fir post, 3 ft. long, 3" sq. 24" in the ground, for ¼ sec. cor., mkd ¼ S. on N face, from which A cedar, 16" dia., bears N.½°E., 22 lks., mkd: ¼ S BT. A laurel, 9" dia., bears S.4¼°E., 21 lks., mkd: ¼ S BT.</p>
<p>GLO resurvey by Wm. M. Bushey under Contract #620 dated June 17, 1893 (DCSO records, Vol. 17 Pages 7126)</p> <p>-----</p> <p>A point 9 lks. South of the ¼ sec. cor. which is a post, 3" sq., firmly set, marked ¼ S on N face, from which A cedar, 16" dia., bears N.½°E., 22 lks., mkd: ¼ S BT. The witness tree in Sec. 6 is destroyed. In its stead, I mark: A fir, 12" dia., bears S.58½°W., 35¾ lks., mkd: ¼ S BT.</p>
<p>Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2013 - M 166-6 & C.S. File 65/81-1</p> <p>-----</p> <p>Set - 5/8"x40" iron rod with 2½" alum. cap mkd: LONE ROCK TIMBER T30S R4W ¼ S31 2013 PLS2291 21" D.Fir bears N.14¼°W., 22.2 ft we scribed T30S R4W ¼ S31 BT and tagged tree. 21" D.Fir bears N.30½°E., 35.4 ft we scribed T30S R4W ¼ S31 BT and tagged tree. Corner lies on steep Southwest slope. Put metal fence post approx. 1.0 ft North of corner.</p>
<p>BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23838)</p> <p>-----</p> <p>The ¼ cor of sec. 31 only, established by Hoffine, in 2013; and is accepted as the cor.; monumented with an iron rod, 5/8" diam., firmly set projecting 4" above ground, with an aluminum cap (properly) mkd. from which the bearing trees mkd. by Hoffine Continued next page</p>

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 23" dia., bears N.30¾°E., 35.4 ft., with scribe marks S31 BT and other illegible scribe marks visible on partially healed blaze.

A fir, 17" dia., bears N.14°W., 1 22.2 ft., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron rod 36" long with brass cap mkd.

T30S R4W
1/4 S 31
T31S R4W
2017