

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7004)

Set ¼ sec. post at proper distance, from which
A B.Oak 30" dia., bears N.80°E., 75 lks. dist.
A B.Oak 20" dia., bears S.20°E., 35 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7088)

The post set for this corner is gone, but both the bearing trees are standing. I restore this corner by setting a Cedar post, 3 ft. long, 3" sq., 24" in the ground, marked ¼ S. on N. face, from which

A B.Oak 30" dia., bears S.20°W., 35 lks. dist. mkd. ¼ S BT
A B.Oak 36" dia., bears N.80°E., 75 lks. dist. mkd. ¼ S BT
These are the old bearing trees, whose marks being overgrown, I renew.

Survey by John H. Markham, Jr. - Wit: B.E. Blomgren - For: Stomar Lumber Co. - June 1953 - C.S. File 41/161-8

Determined by original BTs:
40" B.Oak stump bears N.84°E., 50.0 ft., found old scribe.
30" B.Oak stump bears S.20°E., 23.0 ft., found old scribe.
At corner point, Set 3/4" x 96" Iron pipe with metal plate on top mkd. "¼ 18|19", from which
A 10" B.Oak bears N.17°W., 78.0 ft. mkd. ¼ S18 2880 BT.
A 9" Laurel bears S.40°E., 63.0 ft. mkd. ¼ S19 T30S R4W 2880 BT.
A steel gate bears S.69°W., 95.0 ft.
Power pole #12/33 bears S.69°W., 115.0 ft.
SE. Cor. Claim #37 bears South 33.0 ft. and East 314 ft.
A 3-way fence bears S.28°E., 41 ft.