

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 147100

PRIMARY CORNER DESCRIPTION Angle point on So. Bdy. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6985)

Set ¼ sec. post at proper distance; from which
A Laurel 6" dia., bears N.55°E., 6 lks. dist.
A Laurel 6" dia., bears S.5°W., 12 lks. dist.

(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W., on the offset Meridian Line, - - - -" (V. Laugen, March 1996)

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7023)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S. on N. face, from which
A Cedar 16" dia., bears N.½°E., 22 lks. dist. mkd. ¼ S BT.
A Laurel 9" dia., bears S.4½°E., 21 lks. dist. mkd. ¼ S BT.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7126)

¼ Sec. cor., which is a post, 3" sq., firmly set, marked ¼ S. on N. face, from which
A Cedar 16" dia., bears N.½°E., 22 lks. dist. mkd. ¼ S BT.
The witness tree in Sec. 6 is destroyed. In its stead, I mark
A Fir 12" dia., bears S.58½°W., 35 ¾ lks. dist. mkd. ¼ S BT.

(This corner is now an angle point, due to closing corners being established for secs. 31 and 32; 5 & 6, T31-4. V. Laugen, March 1996)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23837-8)

Point for the original ¼ sec. cor. of secs. 6 & 31, at proportionate dist.; bet. the angle point bet. secs. 5 & 32, formerly the original cor. of secs 5, 6, 31 & 32, and the original closing cor. bet. Tps. 30 & 31 S., R. 4 W. there is no remaining evidence of the original cor. This point now becomes an angle point. Continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 147100

PRIMARY CORNER DESCRIPTION Angle point on So. Bdy. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

AP
T30S R4W
S31
S 6
T31S
2017

from which

A fir, 14" dia., bears N.15¼°E., 17.9 ft., mkd. AP S31 BT.
A fir, 11" dia., bears S.77¼°E., 26.4 ft., mkd. AP S6 BT.