

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7124)

Set a stone 16x8x8 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face; from which

A Maple 12" dia., bears S.52°W., 30½ lks. mkd. ¼ S BT.

A Fir 10" dia., bears N.44½°E., 53 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - John M. Powell, Deputy - Dec. 10, 1971 - C.S. File 53/26-98

Found - Stone, marked ¼ chopped off. Rock in ground approx. right size.

Burnt roots of Maple, S.52°W., 20.1 ft.

No trace of NE. BT.

Call of 5.50 chains hits good by pacing. I do not agree with survey M 21-33 and record distance 497.6 ft. I chain both ways for 562.0 ft. Old axe work on tree North of corner ¼ chopped in bark, also squared post by rock.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 4 W

¼ S31|S32

1971

Replaced corner stone along side brass cap.

New BTs -50" D.Fir S.6°E., 26.5 ft. "¼ S32 CS BT", barks scribed.

14" D.Fir N.53°W., 16.0 ft. scribed "¼ S31 CS BT".

Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2013 - M 166-6 & C.S. File 65/81-1

Condition report only

Found - 1971 Douglas County cap 0.8 ft above ground.

50" D.Fir bears S.7¾°E., 26.7 ft (record S.6°E., 26.5 ft) visible scribing and tag.

28" D.Fir bears N.53½°W., 14.7 ft (record N.53°W., 16.0 ft) healed face and tag

Corner lies on extremely steep East facing slope

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23849)

The ¼ sec. cor. of secs. 31 & 32, perpetuated by Powell, in 1971; from original evidence no longer in existence; monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the BTs mkd. by Powell
A fir, 65" dia., bears S.7 $\frac{3}{4}$ °E., 26.2 ft., with scribe marks $\frac{1}{4}$ S32 CS BT visible on bark.
A fir, 30" dia., bears N.53 $\frac{1}{4}$ °W., 15.1 ft., with a healed blaze.