

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7121)

-----  
Set a stone 12x12x5 ins., 8" in the ground for ¼ sec. cor., marked ¼ on W. face, from which

A Fir 15" dia., bears N.85°W., 31 lks. dist. mkd. ¼ S BT.

A Fir 15" dia., bears S.13¼°E., 28 lks. dist. mkd. ¼ S BT.

John H. Markham, Jr. - April 5, 1949 - C.S. 40/179-1

-----  
Determined from the remains of the old bearing trees:

Burnt stump, bears N.85°W., 31 lks.

Stump hole, bears S.13°E., 28 lks.

At corner point, Set 4" Alder post, from which

Alder 8" dia., bears N.28°E., 52 ft., scribed ¼ S 2880 BT.

Fir 16" dia., bears N.3°E., 141 ft. scribed ¼ S 2880 BT.

This cor. is 221 ft. South of Beals Creek; there are three old fences running N., E., and W. from this corner; the post being 12 ft. South of fence corner.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - June/July 1963 - C.S. 53/26-63

-----  
Found - Post at corner. Also 1¼" I.P., not recorded.  
8" Alder N.28°E., 52.0 ft., OK, now 12", rescribed "¼ S30 CS BT"

16" Fir N.3°E., 141.0 ft., snag, shows scribing.

New BT - 6" Fir N.74°W., 7.5 ft. scribed ¼ S29 CS BT.

Fd. OK, May 1991 - M 113-18

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23844)

-----  
The ¼ sec cor. of secs. 29 & 30, perpetuated by Markham Jr., in 1949; subsequently perpetuated by Byron in 1963; from original evidence no longer in existence; monumented with an iron pipe, 1½" dia., firmly set, projecting 9" above ground.

At the corner point

Set a stainless steel post, 28" long, 2½" dia. 26" in the ground, directly over the iron pipe, 28" long, w/brass cap mkd

T30S R4W

¼

S30|S29

2017

from which

A fir, 10" dia., bears N.67¾° E., 30.9 ft., mkd. ¼ S29 BT.

A fir, 9" dia., bears N.45½° W., 56.1 ft., mkd. ¼ S30 BT.