

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7004)

-----  
Set ¼ sec. post, from which  
A Laurel 5" dia., bears S.20°W., 25 lks. dist.  
A B.Oak 4" dia., bears S.30°E., 25 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7085-86)

-----  
The post of this corner is gone, but both the old bearing trees are standing. I restore this corner by setting a basalt stone 16x10x7 ins. marked ¼ on W. face, in a mound of stone, from which  
A B.Oak 7" dia., bears S.30°E., 25 lks. dist. mkd. ¼ S BT  
A Laurel 8" dia., bears S.20°W., 43 lks. dist. mkd. ¼ S BT.  
These are the old bearing trees, whose marks being partially overgrown, I renew.

Survey by John H. Markham, Jr. - Wit: B.E. Blomgren - For: Stomar Lumber Co. - June 10, 1953 - C.S. File 41/161-7

-----  
Determined by O.B.T. At cor. point, found 3 ft. pile of stones and drove 1" x 30" Iron pipe, from which  
A 12" Laurel snag bears S.10°W., 28.0 ft., found scribe.  
An 8" Pine bears S.11°W., 17.0 ft. mkd. ¼ S BT.  
A 12" Laurel bears N.6°W., 64.0 ft. mkd. ¼ S BT.  
A 16" Laurel bears N.48°E., 68.0 ft. mkd. ¼ S20 T30S R4W 2880 BT.  
Fences run E and W. from corner. Cor. lies top of spur ridge.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - July 1963 - C.S. File 53/26-81

-----  
Found - Stone and I.Pipe at corner. All three BTs, now down. Pine to SW. shows scribing.  
New BTs -10" Pine S.62°W., 54.3 ft. scribed ¼ S19 CS BT.  
12" Fir N.31°E., 57.2 ft. scribed ¼ S20 CS BT.  
Fence E., W., and S. from corner.