

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7005)

Set post cor. of secs. 7, 8, 17 and 18.
Made trench and drove charged (*charred?*) stake in center as per instructions.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7089)

The post set for this corner is gone, and cultivation has obliterated the marks of a trench. I therefore run North, and intersect ¼ sec. cor. between secs. 7 & 8, at post. (Note: this is the best line I have found in true bearing and chaining; I believe that it is the second line run by Deputy Ford in subdividing) This established the position in the N. and S. line, as neither of the closing lines W. and E., with bearings described in the field notes of original survey could be depended upon. I had recourse to the field notes of survey of DLC #42. I went to the NW. corner of said claim and run South 17.38 chs., set a temp. post at 56.95 chs., intersect ¼ sec. post, developing my measure to be shorter 26 lks. than the original survey, making a proportionate difference of 18 lks.

I set 8 lks. N. of temp. post for cor. to secs. 7, 8, 17 and 18, A basalt stone 9x8x8 ins., marked with 4 notches on S. and 5 notches on E. edges, 6" in the ground, and raised a mound of stone, from which

A Willow 6" dia., bears S.75 3/4°E., 2.00 chs. dist. mkd.
T30S R4W S17 BT.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20120)

Point for the cor. of secs. 7, 8, 17 & 18, at proportionate dist., determined by the irregular boundary method between the original cor. of secs. 17, 18, 19 & 20 and the reestablished NW. cor. of DLC # 42, there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 46" in the ground, with brass cap mkd.

T30S	R4W
<u>S 7</u>	<u>S 8</u>
S 18	S 17
1994	

continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No suitable accessories available
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the reestablished NE. cor. of Donation Land Claim No. 41, bears N.0°00'41"E., 12.454 chs., hereinafter described.

From this same point, the ¼ sec. cor. of secs. 7 & 8, perpetuated by Byron, in 1963, from original evidence no longer in existence, bears N.0°38'16"E., 40.643 chs.; monumented with an iron post, 1½" diam., firmly set, projecting 12" above ground, with brass cap mkd. T30S R4W ¼ S7 S8 1963, from which the remains of bearing trees mkd. by Byron:

A fir snag, 17" diam., bears S.14°E., 29 lks., with healed double blaze.

An oak snag, 15" diam., bears S.33¼°W., 36½ lks. dist., with healed double blaze.

and new bearing trees

A fir, 23" diam., bears N.75½°E., 57 lks., mkd. ¼ S8 BT.

A fir, 38" diam., bears S.59½°W., 61 lks., mkd. ¼ S7 BT.