

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7006)

Set ¼ sec. post, from which
A B.Oak 18" dia., bears N.65°E., 127 lks. dist.
A W.Oak 18" dia., bears N.20°W., 405 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7093)

The old post is gone, but both bearing trees are standing, I restore the cor. by setting an Oak post 3½ ft. long, 4" sq., 24" in the ground, marked S. on W. face, from which
A B.Oak 24" dia., bears N.65°E., 127 lks. mkd. ¼ S BT
A W.Oak 20" dia., bears N.20°W., 405 lks. mkd. ¼ S BT.
These are old bearing trees, which I remark.

Survey by John H. Markham, Jr. - Wit: J.D. Phillips - For: Stomar Lumber Co. - Cot. 26, 1954 - C.S. File 41/308

Determined by:
Orig. BT, 30" B.Oak stump 6 ft. high & alive, bears N.65°E., 83. ft.
Orig. BT, 30" W.Oak bears N.20°W., 327.0 ft.
At corner point, Set 1/2" x 20" reinforcing rod and pile of stones, from which
A 15" W.Oak bears N.18°E., 80.0 ft. mkd. ¼ S8 BT.
A 33" B.Oak bears S.65°W., 68.0 ft. mkd. ¼ S7 BT.
A fence line bears South, 137 ft.
Corner lies 137 ft. North of 100 acre field in So. Umpqua bottom.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-89

Found - Original now 32" W.oak N.20°W., 267.3 ft. We open and find good scribing.
Part of shell and remains of orig. BT to East. Find bearing should be S.65°E., 83.8 ft., not N.65°E., 83.8 ft., as it would then check record bearing and distance to NW. BT.
John Markham's corner bears South, 65.4 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 4 W
¼ S7|S8
1963
New BTs -6" R.Fir bears S.12°E., 18.8 ft. scribed ¼ S8 CS BT.
12" B.Oak bears S.36°W., 24.4 ft. scribed ¼ S7 CSBT.
Cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20120)

From this same point, the ¼ sec. cor. of secs. 7 & 8, perpetuated by Byron, in 1963, from original evidence no longer in existence, bears N. 0° 38' 16" E., 40.643 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T30S R4W 1/4 S7 S8 1963, from which the remains of bearing trees mkd. by Byron:

A fir snag, 17" diam., bears S. 14° E., 29 lks. with healed double blaze.

An oak snag, 15" diam., bears S.33¼°W., 36½ lks. with healed double blaze.

and new bearing trees

A fir, 23" diam., bears N.75½°E., 57 lks., mkd. ¼ S8 BT.

A fir, 38" diam., bears S.59½°W., 61 lks., mkd. ¼ S7 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 26, 1998 - C.S. File 66/4-7

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground, properly marked. 1963 ½" x 16" long iron rod is found out of ground approx. 12 ft. Westerly and down hill of record position. (South 65.4 ft.) as noted in 1963 DCSO renewal set in error in 1954.

No OBTs found.

6" now 17" dia., 10 ft high D.Fir snag, with a fully healed double blaze, bears S.12°E., 18.8 ft. (Agrees with 1963 DCSO rec.) 1963

12" now 14" dia., mostly dead B.Oak, with a fully healed double blaze, bears S.33¼°W., 24.1 ft. (Agrees with 1994 BLM rec.) 1963

38" now 39" dia., D.Fir, with a fully healed single blaze, bears S.59½°W., 40.3 ft. (Agrees with 1994 rec.) 1994

23" now 25" dia., mostly dead, D.Fir with a fully healed single blaze, bears N.75½°E., 37.6 ft. (Agrees with rec.) 1994

New BTs- 20" dia., D.Fir, double blazed and scribed "¼ S8 CS BT" bears S.29°E., 49.8 ft.

30" dia., Pine, double blazed and scribed "¼ S7 CS BT" bears N.5½°W., 237.0 ft.

See sketch in file.