

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7006)

Set post cor. of secs. 5, 6, 7 and 8, from which
A B.Oak 6" dia., bears S.55°E., 85 lks. dist.
A B.Oak 14" dia., bears N.65°E., 60 lks. dist.
A B.Oak 12" dia., bears N.15°W., 295 lks. dist.
A W.Oak 15" dia., bears S.88°W., 66 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Pgs 7092-93)

The post set for this corner is gone, but three bearing trees are standing. I restore by setting an Oak post 4 ft. long, 4" sq., 24" in the ground, marked T30S S5 on NE.; R4W S8 on SE.; S7 on SW.; and S6 on NW. faces, with 5 notches on S. and E. edges, from which

- A B.Oak 20" dia., bears N.65°E., 60 lks. dist. mkd. T30S R4W S5 BT.
- A B.Oak 10" dia., bears S.55°E., 85 lks. dist. mkd. T30S R4W S8 BT.
- A B.Oak 16" dia., bears N.15°W., 295 lks. dist. mkd. T30S R4W S6 BT.

These are the original bearing trees, which I remark, the old marks being overgrown, also

- A W.Oak 20" dia., bears N.88°W., 60 lks. dist., instead of S.88°W., as described in the field notes furnished me, this tree standing Sec. 6, already supplied.
- I mark a Laurel 6" dia., bears S.52¼°W., 33 lks. dist. mkd. T30S R4W S7 BT.

John H. Markham, Jr. - July 25, 1951 - C.S. File 40/179-6

Found - B.Oak 26" dia., bears N.65°E., 40.0 ft., remarked S.C. S6 BT.
B.Oak 10" dia., bears S.55°E., 56.0 ft., remarked S.C. S8 BT.
W.Oak 22" dia., bears N.88°W., 40.0 ft. remarked S.C. S5 BT.
Laurel 8" dia., bears S.52°W., 22 ft., remarked S.C. S7 BT.

At corner point, Set 1" x 30" Iron pipe, from which:
1/4 Cor. bears North, 2610 ft.
1/4 Cor. bears West, 25.40 ft.
1/4 Cor. bears East 2695 ft.

There is a fence running East and West from corner.

continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-55

Found - 1" I.P. at corner.
Orig. NW. BT, now dead, shows good scribing.
Orig. NE. BT, now stump.
SW BT, now stump.
10" now 14" B.Oak S.55°E., 56.0 ft., fair condition.
New BTs - 8" B.Oak bears N.8°E., 78.9 ft. scribed S5 T30S R4W CS BT.
12" Laurel bears N.2°W., 76.8 ft. scribed S6 T30S R4W CS BT.
10" B.Oak bears S.44°W., 30.0 ft. scribed S7 CS BT.

Fd. IP & NW Oak, OBT, Ronald Quimby - April 1999 - M 129-44

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/17/2000 - C.S. File 66/16-22

Found - 1" I.D. iron pipe bent & leaning 18" east of plumb, protrudes 6" out of ground. (1951)
15" W.Oak now 18" dia., 2½ ft. high rotted stump, no scribing visible, bears N.88°W., 40.0 ft. OBT
14" B.Oak, now scattered rotted remains of an Oak "N.65°E., 40 ft." not measured. OBT?
12" now 20" dia., 1 ft. high Madrone stump no marks, bears N.2°W., 76.8 ft. 1963
New - 19" dia., I.Cedar single blazed & scribed "T30S R4W S6 CS BT" bears N.89°W., 14.2 ft.
8" dia., Madrone bark scribed "T30S R4W S7 CS BT" bears S.29½°W., 51.9 ft.
11" dia., Maple double blazed & scribed "T30S R4W S6 CS BT" bears N.13°W., 76.4 ft.
17" dia., D.Fir double blazed & scribed "T30S R4W S4 CS BT", bears N.85½°E., 53.8 ft.
Set - Plumb position of 1951 IP referenced, removed I.P. measured 26" long, a 2 3/8" dia. BC on a 1 3/8" O.D. by 32" long IP is set at ref. corner position, protrudes 5" out of ground. 1951 IP set along east edge of BC/IP, protrudes 4" out of ground. Cap mkd: DOUGLAS COUNTY SURVEYORS OFFICE

T30S
S6|S5 R
S7|S8 4
2000 W

Note - Corner is 4 ft. south of an E-W fence line. Evidence of old fence wire found at corner.