

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7004)

-----  
Set ¼ sec. post at average distance, from which  
A Laurel 20" dia., bears N.75°W., 24 lks. dist.  
A B.Oak 4" dia., bears N.60°E., 57 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7087)

-----  
Set a Maple post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S. on N. face, from which  
A Maple 5" dia., bears S.24°W., 32 lks. dist. mkd. ¼ S BT  
A Fir 15" dia., bears N.40°E., 29 lks. dist. mkd. ¼ S BT.  
The old post and bearing trees are gone, there are no oaks growing here now, fire has been through here.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-82

-----  
Found - Original 15" now 30" R.Fir N.40°E., 19.1 ft. We open and find good scribing.  
Original SW. BT, not found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 4 W  
¼ S 17  
S 20  
1963

New BTs -Rescribe now 30" R.Fir N.40°E., 19.0 ft. "¼ S17 CSBT".  
9" Maple bears S.31°W., 20.8 ft. scribed ¼ S20 CS BT.

Fd. Ok by BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20117)