

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 247100

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6985)

Set ¼ sec. post at proper distance, from which
A Laurel 10" dia., bears S.65°E., 17 lks. dist.
A Laurel 4" dia., bears N.50°E., 37 lks. dist.

(Note: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the offset Meridian line, - - - - - .") V. Laugen, March 1996

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7022)

Set a Dogwood post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N. face, from which
A Maple 6" dia., bears N.18°W., 16 lks. dist. mkd. ¼ S BT.
A Maple 9" dia., bears S.12°E., 27 lks. dist. mkd. ¼ S BT.

Cor. Fd. and tied by Wm. M. Bushey, Contract #620, dated June 17, 1893 - (DCSO records, Vol. 17 Pg. 7125)

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18132-33)

Point for the ¼ sec. cor. of secs. 5 and 32, determined by irregular boundary method; there is no remaining evidence of the original corner, this point now becomes an angle point. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. AP
T 30 S R 4 W
S 32

S 5
T 31 S
1985

from which
A Fir 31" dia., bears N.7¼°E., 72½ lks. dist. mkd. AP S32 BT.
A Fir 14" dia., bears S.80°E., 94½ lks. dist. mkd. AP S5 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
The corner is located on steep NW. slope.

Cont.

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 247100

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23834-5)

An angle point bet. secs. 5 and 32; formerly the ¼ sec. cor. of secs. 5 and 32, monumented with a magnet in a white plastic case buried 4" below the surface of the ground, from which the remains of a BT mkd. by Rogers, McMullen, and Bishop in 1984-86

A burnt and decayed fir stump, 32" dia., bears N.7¼°E., 47.9 ft., with scribe marks AP visible on a separated fragment of the blaze lying alongside.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd

AP

T30S R4W

S 32

S 5

T31S

2017

from which

A fir, 9" dia. bears N.5¾°E., 8.3 ft., mkd. AP S32 BT.

A fir, 11" dia., bears S.39¼°W., 41.6 ft., mkd. AP S5 BT.

Deposit the magnet at the base of the stainless steel post.