

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7118)

Set a stone 14x12x12", 10" in the ground for ¼ sec. cor. marked ¼ on N face; from which

A fir 12" dia., bears S.54½°E., 35 lks., mkd: ¼ S BT.

A maple, 10" dia., bears N.30¼°W., 2 lks., mkd: ¼ S BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23842-3)

Point for the ¼ sec. cor. of secs. 32 & 33 at proportionate measurement; there is no remaining evidence of the orig. cor. Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T30S R4W

¼

S32|S33

2017

from which

A fir, 26" dia., bears N.76¾°E., 30.2 ft., mkd. ¼ S33 BT.

A fir, 22" dia., bears N.5¾°W., 34.4 ft., mkd. ¼ S32 BT.