

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7116)

Set a stone 16x14x6 ins., 12" in the ground, for cor. to secs. 28, 29, 32 and 33, marked with 4 notches on E. and 1 notch on S. edges; from which

A Fir 36" dia., bears N.79°E., 136 lks. dist. mkd. T30S R4W S28 BT.

A Fir 30" dia., bears S.74½°E., 163 lks. dist. mkd. T30S R4W S33 BT.

A Fir 40" dia., bears S.89°W., 84½ lks. dist. mkd. T30S R4W S32 BT.

A Fir 26" dia., bears N.68¼°W., 70 lks. dist. mkd. T30S R4W S29 BT.

Survey by John H. Markham, Jr. - June 24, 1961 - C.S. File 42/356-25

Determined by O.B.Ts:

42" Fir N.79°E., 89.8 ft.

32" dead Fir N.68°W., 46.2 ft.

40" dead Fir S.89°W., 55.8 ft.

At corner point found stone, and Set 3/4" x 30" Iron pipe, from which

9" Laurel bears N.64°W., 12.6 ft. mkd. S29 T30S R4W BT.

10" Fir N.47°E., 6.5 ft. mkd. S28 BT.

17" Fir S.31°E., 9.7 ft. mkd. S33 BT.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 7/2004 - M 145-20

Found - 1½" iron pipe out of position with adjacent post
Set - 5/8" x 30" rebar with 2½" aluminum cap marked

T30S R4W

29|28

32|33

2004

54633LS

42" fir stump bears N.79½°E, 93.3' (record 89.8,) (healed face)

10" D.Fir stump bears N.75½°E, (record N.47°E.) 6.5' (healed face with Metal cap on stump)

17" D.Fir stump bears S.44°E, (record S.31°E.) 9.7' (healed face with Metal cap on stump)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23841-2)

The cor. of secs. 28, 29, 32, & 33, perpetuated by Markham Jr., in 1961; subsequently perpetuated by Rice, in 2004; monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above ground (alongside of which is an iron pipe, 1" dia., 24" long, lying loose on the ground), with an aluminum cap (properly) mkd.

from which the remains of the original BTs

A fir stump, 43" dia., bears N.79°E., 93.2 ft., with a healed blaze. (Record, 89.8 ft.)

A decayed fir stump, size indeterminate, bears N.73¾°W., 46.2 ft., no marks visible. (Record bears N.68¾°W.)

and the remains of the BTs mkd. by Markham

A decayed fir snag, 10" dia., bears N.72½°E., 6.5 ft., alongside of which is a tin-capped down fir trunk segment, with a healed blaze.

A tin-capped decayed fir stump, 18" dia., bears S.39°E., 10.0 ft., no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, 30" long, with brass cap mkd

T30S R4W
S29|S28
S32|S33
2017

from which

A fir, 6" dia., bears N.45¾°E., 17.3 ft., mkd. T30S R4W S28 BT.

A fir, 9" dia., bears S.84°E., 25.9 ft., mkd. T30S R4W S33 BT.

A fir, 5" dia., bears S.24½°W., 19.6 ft., mkd. T30S R4W S32 BT.

A fir, 7" dia., bears N.37½°W., 18.2 ft., mkd. T30S R4W S29 BT.

Buried the iron pipe, 24" long, alongside the stainless steel post.