

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6993)

-----  
Set post at average distance cor. of secs. 20, 21, 28 and 29, from which

- A B.Oak 10" dia., bears S.87°E., 8 lks. dist.
- A B.Oak 12" dia., bears N.75°E., 20 lks. dist.
- A W.Oak 10" dia., bears N.2°W., 18 lks. dist.
- A B.Oak 18" dia., bears S.3°W., 16 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7068-69)

-----  
At sec.cor., Here I find three bearing trees, namely a B.Oa, 25" dia., mkd. S20 BT, and a W.Oak 22" dia., mkd. S21 BT, within 10 lks. of each other, E. and W., also a W.Oak 10" dia., mkd. S28 BT. But the distances given in the field notes are totally wrong. I also find the remains of a fence, built probably 25 years ago, running N. and S., also a later built fence, course E. and W. By taking the intersection of these fences, which were probably built when the original corner post stood, I find bearing tree N.2°W. to stand 184 lks. instead of 18; bearing tree Sec. 28, 84 lks. dist., instead of 8 lks. This point is also verified by running from ¼ sec. post between secs. 20 and 21, S.1°W., (equal to S. of Deputy Ford's surveys) 38.90 chs. There are also some Oak trees with old blazes E. and W. of this point. I restore this corner by setting a basalt rock 12x8x6 ins., marked with 2 notches on S. and 4 notches on E. edges, in a mound of stone, from which

- A B.Oak 25" dia., bears N.2°W., 184 lks. dist. mkd. T30S R4W S20 BT.
- A W.Oak 22" dia., bears N.3°E., 192 lks. dist. mkd. T30S R4W S21 BT.
- A W.Oak 10" dia., bears S.34°E., 84 lks. dist. mkd. T30S R4W S28 BT.

(These are the old bearing trees, which I remark.)

- A W.Oak 4" dia., bears S.6°W., 53 lks. dist. mkd. T30S R4W S29 BT.

Survey by John H. Markham, Jr. - Wit: B.E. Blomgren - For: Stomar Lbr. Co. - June 2, 1953 - C.S. File 41/161-3

-----  
Determined by O.B.T.:  
35" B.Oak bears N.2°W., 121.0 ft.  
26" W.Oak bears N.3°E., 126.0 ft.  
(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" W.Oak bears S.34°E., 55.0 ft.  
At corner point, Set 1" x 30" axle with 6½" flange up, from which  
An 8" W.Oak bears S.42°E., 23.4 ft. mkd. S28 BT.  
A 10" W.Oak bears N.54°W., 18.2 ft. mkd. S20 BT.  
A 12" W.Oak bears N.17°E., 13.0 ft. mkd. S21 BT.  
Fence corner bears N.77°W., 25.0 ft.

Douglas Co. Surveyors Office - James Byron - 6/1963 (added 8/25/2016) - C.S. File 53/26-67  
-----  
Fd. Cor. OK

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23850)  
-----  
The cor. of secs. 20, 21, 28, & 29, subsequently perpetuated by Markham, in 1953; from original evidence no longer in existence; monumented with an axle shaft, 1" dia., with a 6 hole steel flange, 7" dia., firmly set, with top flush with the surface of the ground, from which BTs mkd. by Markham  
An oak, 20" dia., bears N.14¾°E., 13.5 ft., with a healed blaze.  
An oak, 16" dia., bears S.39¾°E., 23.2 ft., with a healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, directly over the inverted axle shaft, 24" long, with brass cap mkd.  
$$\begin{array}{r} T30S R4W \\ \hline S20|S21 \\ \hline S29|S28 \\ 2017 \end{array}$$
  
NAD 1983 (2011)  
Latitude: 42°56'27.94" N.      Longitude: 123°11'20.60" W.