

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7001)

Set a post cor. of secs. 16, 17, 20 and 21, from which
A Red Fir 5" dia., bears S.75°W., 11 lks. dist.
A Laurel 4" dia., bears S.65°E., 25 lks. dist.
A Red Fir 6" dia., bears N.30°E., 10 lks. dist.
A B.Oak 8" dia., bears N.60°W., 13 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7071-72)

The post set for this corner is gone; all the bearing trees but the B.Oak in Sec. 17 have been destroyed by fire a long time ago, but this B.Oak shows yet BT., also partly burnt. I restore this corner by setting a Fir post, 4 ft. long, 4½" sq., 24" in the ground, mkd. T30S S16 on NE.; R4W S21 on SE.; S20 on SW.; S17 on NW. faces with 3 notches on S., and 4 notches on E. edges, from which
A B.Oak 16" dia., bears N.60°W., 13 lks. dist. mkd. T30S R4W S17 BT. This is the old bearing tree, which I remark.
A Fir 14" dia., bears N.20°E., 10 lks. dist. mkd. T30S R4W S16 BT.
A Fir 18" dia., bears S.47½°E., 19 lks. dist. mkd. T30S R4W S21 BT.
A B.Oak 6" dia., bears S.73°W., 11 lks. dist. mkd. T30S R4W S20 BT.

Survey by Willis M. Ausland - For: Al Roe - Jan. 1942 - Vol. 4 Pg. 84; C.S. File 36/17; C.S. File 30/49

Set gun barrel for section corner from 2 witness trees:
28" Fir N.20°E., 10 lks., good shape.
30" Fir N.47½°E., 19 lks., good shape.
New witness trees:
20" Fir S.74°W., 22.0 ft.
8" Fir S.18°W., 36.5 ft.

James W. Byron - For: G. Neuner; E. Smner and A. Rowe - Jan. 17, 1955 - C.S. File 46/83 (pg 2-3)

BTs OK except 20" Fir, S.74°W. has been cut, stump only left.
Gun barrel in place.
Blazed and scribed:
10" R.Fir, N.9°W., 36.0 ft. (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - July 1963 - C.S. File 53/26-82

Found - Gun barrel at corner and all BTs as recorded, except 9" Fir, N.9°W., 36.0 ft. which is now snag.

New BT - 20" B.Oak bears N.85°W., 73.3 ft. scribed S17 T30S R4W CS BT.

Logging road 90 ft. West of corner.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20108-9)

The cor. of secs. 16, 17, 20 & 21, perpetuated by Ausland, in 1942, recorded in 1958, further perpetuated by Byron, in 1955 and 1963; monumented with a gun barrel, firmly set, projecting 6" above ground, from which the remaining original bearing trees:

A fir, 28" diam., bears N.20°E., 15½ lks., with partially healed blaze. (Record, 10 lks.)

A fir, 36" diam., bears S.64¼°E., 17 lks., with healed double blazes. (Record, S.47½°E., 19 lks.)

and the remains of a bearing tree mkd. by Byron in 1955

A root hole, bears N.10¼°W., 54 lks., with decayed fir trunk, size indeterminate, laying alongside.

and a bearing tree mkd. by Byron in 1963

An oak, 18" diam., bears N.87 3/4°W., 111 lks. with healed double blazes.

At the corner point.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, directly over the gun barrel, with brass cap mkd.

T30S	R4W
S 17	S 16
S 20	S 21
1994	

from which new bearing trees

A fir, 11" diam., bears S.83°W., 85 lks., mkd. T30S R4W S20 BT.

A fir, 6" diam. bears N.5°W., 76 lks. mkd. T30S R4W S17 BT

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.