

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7001-02)

Set post cor. of secs. 8, 9, 16 and 17, from which
A W.Oak 15" dia., bears S.10°W., 436 lks. dist.
No other trees in reasonable distance.
Made trench as per instructions.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7074)

The post set for this corner is gone, the only bearing tree has been cut down, but the log still shows survey or marks. I am informed that this has been the original bearing tree. It is the stump of a W.Oak 18" dia.; the marks showing it to have stood in Sec. 17. I restore this corner by setting a basalt rock 10x8x7 ins., 7" in the ground, marked with 4 notches on S. and E. edges; raised a mound of stone along side, from which
A W.Oak 15" dia., bears S.55°E., 384 lks. dist. mkd. T30S R4W S16 BT.
A W.Oak 6" dia., bears S.5 3/4°W., 272 lks. dist. mkd. T30S R4W S17 BT.

No trees in Sec. 8 and 9, within 20 chs. The position of this corner was afterwards verified by running from the interior corner of DLC #44, North 20 chs. and E. 20 chains, agreeing with field notes of survey of said claim.

F.C. Frear - Wit: J. Metz; W.C. Pickens - March 11, 1919 - Vol. 3 Pg. 56; Field Book 15 Pg. 46

Set in a 2" x 36" Iron pipe and a 4" x 48" Oak stake, from which
A 24" W.Oak bears S.53°55'E., 2.84 chs.
A 10" W.Oak bears S.7¼°W., 2.72 chs.

B. Irving, County Surveyor - Wit: G. Richardson; E. Godfrey; S. Kershner - Jan. 26, 1948 - M26-75 & C.S. File 39/155

Set a 1" Iron pipe with a brass cap marked: "County Surveyor T30S R4W 8, 9, 16, 17" with the following witness trees:
20" W.Oak bearing S.13°00'E., 174.92 ft. dist.
Remarked a 12" Oak marked by Eppstein. (S.7°15'W., 179.5' M26-75 on M26-75 - added 8/20/2024)

Fd. B.C. and SE BT, Feb. 1994 by L. Maddux - M 118-48

continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20121-2)

From the cor. of secs. 8, 9, 16 & 17, perpetuated by Frear, in 1919, from original evidence no longer in existence, further perpetuated by Irving, in 1948, monumented with an iron post, 1½" diam., firmly set flush with the ground, with brass cap mkd. (brass cap is oriented to the east):

T30S
9 16
8 17

R4W

from which a bearing tree mkd. by Irving

An oak, 20" diam., bears S.14 3/4°E., 263 lks., with healed double blaze.

No other suitable accessories available

The corner is located at a fence corner, with woven wire fences extending N., S., and W.

Latitude 42°58'09.86"N

Longitude 123°11'12.65"W

(NAD 1927)

(added 6/25/2008)