

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7003)

-----  
Set post cor. of secs. 4, 5, 8 and 9, from which  
A B.Oak 4" dia., bears S.2°E., 185 lks. dist.  
A B.Oak 12" dia., bears S.10°W., 190 lks. dist.  
A B.Oak 10" dia., bears N.87½°E., 174 lks. dist.  
A B.Oak 14" dia., bears N.70°W., 117 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7077)

-----  
The post to this corner is gone, but all the bearing trees in Secs. 4, 5 and 8 are standing, so is also a stump of an Oak in Sec. 9, all corresponding in size and direction with the field notes furnished me. I restore this corner by setting a Pine post 4 ft. long, 4" sq., 24" in the ground, marked T30S S4 on NE.; R4W S9 on SE.; S8 on SW.; S5 on NW. faces and 5 notches on S. and 4 notches on E. edges, from which

A B.Oak 12" dia., bears N.87½°E., 174 lks. dist. mkd. T30S R4W S4 BT.  
A B.Oak 8" dia., bears S.14°W., 190 lks. dist. mkd. T30S R4W S8 BT.  
A B.Oak 16" dia., bears N.70°W., 107 lks. dist. mkd. T30S R4W S5 BT.

These are the old bearing trees, whose marks being overgrown, I renew.

A Pine 8" dia., bears S.1½°E., 87 lks. dist. mkd. T30S R4W S9 BT.

George J. Wenderoth, Deputy Co. Surveyor - Frank Loso, Lawrence Michaels, Witnesses - May 23, 1949 - (No record source found, info. from former renewal record #76)

-----  
Found - 18" B.Oak N.87½°E., 114.4 ft., rotten.  
20" B.Oak N.70°W., 70.6 ft., dead.  
Drive 2" Iron pipe for corner, from which I scribe:  
14" B.Oak N.56°15'E., 79.2 ft.  
20" B.Oak S.36°15'E., 87.6 ft.  
14" Pine N.87°50'W., 19.5 ft.  
14' Pine S.37°45'W., 22.0 ft.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20113-4)

-----  
From the cor. of secs. 4, 5, 8 & 9, perpetuated by Wenderoth, in 1949, from original evidence no longer in existence, monumented with an iron pipe, 2½" diam., firmly set, projecting 10" above ground, from which the remaining bearing trees mkd. by Wenderoth:

An oak, 22" diam., bears N.54°E., 121 lks. with healed blaze.

An oak, 20" diam., bears N.82 3/4°E., 172 lks., with healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, with brass cap mkd.

T30S	R4W
S 5	S 4
S 8	S 9
1994	

from which a new bearing tree

A pine, 18" diam., bears S.54°E., 227 lks., mkd. T30S R4W S9 BT.

No suitable accessories available in the SW and NW quadrants Deposit a white "DEEP-1" magnetic marker at base of and iron pipe alongside of stainless steel post.

From this point, U. S. Geological Survey triangulation station BLAND MTN, bears S.73°57'39"E., 288.739 chs. (mean bearing and sea level distance); monumented with a bronze disk, cemented flush in solid rock, with top mkd. "BLAND MTN 1953" and a triangle.

Latitude 42°59'01.35"N

Longitude 123°11'11.20"W

(NAD 1927)

(added 6/25/2008)