

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7117)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on N. face; from which
A Laurel 12" dia., bears S.37¼°W., 28 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears N.3¼°W., 44½ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: J.R. Markham - Aug. 5, 1960 - C.S. File 42/356-23

Determined by O.B.Ts:
15" Fir N.3°W., 29.0 ft., found scribe.
30" Laurel S.37°W., 18.5 ft. I rescribe "¼ S33 BT"
At corner point, Set 1" x 30" I.P., from which
9" Chinquapin bears S.44°E., 23.0 ft. mkd. ¼ S33 BT.
10" Fir bears S.62°W., 24.3 ft. mkd. ¼ S33 BT.
5" Cedar bears S.62°W., 27.6 ft. mkd. ¼ S33 BT.
Top of ridge bears East, 135.0 ft.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. -
7/2004 - M 145-20

Set - 5/8" x 30" rebar with 2-1/2" aluminum cap marked
T30S R4W
¼ $\frac{S\ 28}{S\ 33}$
2004
54633LS
6" D.Fir bears S.76°E. 4.8', blazed & scribed: ¼ S33 BT
15" D.Fir bears S.27°E, 19.2', blazed & scribed: ¼ S33 BT
15" D.Fir bears S.36°W. 18.6', blazed & scribed: ¼ S33 BT
7" D.Fir bears N.78°W. 23.5' blazed & scribed: ¼ S28 BT