

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Frederick E. Warner - For: J.H. Baxter & Co. -
March/April 1957 - C.S. File 42/257

Point for corner located by intersection of N-S and E-W
centerlines of sec.

Set 1½" Iron pipe, 36" long, 28" in ground, mkd. RS 298, from
which

A D.Fir 16" dia., bears N.87°E., 3.96 ft. mkd. C¼ S4 RS
298 BT.

A Cedar 8" dia., bears S.13°30'E., 9.90 ft. mkd. C¼ S4 RS
298 BT.

A D.Fir 8" dia., bears S.45°W., 5.94 ft. mkd. C¼ S4 RS 298
BT.

A Cedar 6" dia., bears N.24°15'W., 9.24 ft. mkd. C¼ S4 RS
298 BT.

Fd. OK May 1959 by M. Ramsey - C.S. File 51/19

Fd. OK, June 1970 by L. Bishop - M 42-1

BLM dependent resurvey by Bryan S. Seibold, Cadastral
Surveyor, and Robert Browning, Surveying Technician, under
Group #1686, surveyed May 1993 thru April. 1995 - (DCS0
records Vol. 52 Page(s) 20137-8)

Point for the center ¼ sec. cor. of sec. 4, at intersection
with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" diam., 24" in the
ground, with brass cap mkd.

T30S R4W
C1/4 S 4
1994

from which

An oak, 25" diam., bears S.30½°E., 65 lks., mkd. C¼ S4 BT.

A fir, 8" diam., bears S.25¼°W., 52 lks., mkd. C¼ S4 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless
steel post.

From this point, a point established as the center ¼ sec.
cor. of sec. 4 by Warner, in 1957, perpetuated by Ramsey, in
1959, bears S.83°13'28"E., 0.230 chs.; monumented with an
iron pipe, 1 ¾" diam., firmly set, projecting 10" above
ground, from which the remains of bearing trees mkd. by
Warner:

A sawed fir stump, 20" diam., bears N.85½°E., 6 lks., with
healed blaze.

A cedar, 10" diam., bears S.14½°E., 15½ lks., with scribe
marks ¼ S4 RS298 BT visible on open blaze.

A fir snag, 8" diam., bears S.46°W., 9 lks., with healed
blaze visible on trunk alongside.

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 10" diam., bears N.24½°W., 14 lks., with scribe marks C¼ S4 RS298 BT visible on open blaze.
This point was rejected due to improper control and not utilized in this survey.

Fd. OK by B. Shaner, Nov. 2001 - 2001-0094 A thru C