

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 376100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 and 4 only, T31-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCS0 records Vol. 18 Page(s) 7834-35)

At a point 3.56 chs. West of the closing cor. to secs. 33 and 34, SET a stone 14x14x10 ins., 10" in the ground for closing cor. to secs. 3 and 4, marked C C on S. face with 3 notches on E. and W. faces; from which
A Fir 5" dia. bears S.41½°E., 18¾ lks. mkd. T31S R4W S3 BT
A Fir 12" dia. bears S.20°W., 74½ lks. mkd. T31S R4W S4 BT
A Fir 16" dia. bears N.47½°W., 29 lks. mkd. T31S R4W CC S3 & 4 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Nov. 17, 1959 - C.S. File 42/391-48

Determined by O.B.T.:
24" Fir bears N.47°W., 19.1 ft. (OBT)
At corner point, SET ½" x 30" angle iron, from which
3" Laurel bears S.7°E., 26.0 ft. mkd. S3 T31S BT.
24" Fir bears S.41°E. 56.0 ft. bark scribed S3 T31S R4W BT
30" Fir bears S.75°E., 57.0 ft. mkd. S3 T31S R4W BT on bark.

Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-19G & M132-37

Found - ½"x½"x30" angle iron, from which
26" D.Fir BT, face overgrown, now a stump with a tin cap, bears S.41°E., 56.0 ft.
36" D.Fir BT, face overgrown, bears N.47°W. 19.1 ft.
30" D.Fir BT, now stump, bears S.75°E., 57.0 ft.
6 ft. steel fence post bears North, 1.0 ft.
Set - ¾"x40" iron rod, with a 2½" alum. cap, over angle iron, mkd: ROSEBURG RESOURCES CO.
T30S R4W WM
33
S 4 | S 3
T31S
2000
LS 430
12" D.Fir BT, I scribed "T31S R4W S4 BT" bears S.70°W., 17.6 ft.

Fd. Ok by Jerry Estabrook, May 2003 C.S. File 65/45-32L & M142-36