

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec cor for 33 & 34 only (So Bdy)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCS0 records Vol. 17 Page(s) 7115)

At a point of intersection, A W.Fir 5" dia., for closing cor. to secs. 33 and 34, which I mark CC T30S R4W on N.; S34 on E.; and S33 on W. faces, with 3 notches on E. and W. faces; from which

An Alder 10" dia., bears N.83½°E., 36½ lks. dist. mkd. T30S R4W S34 BT.

A Fir 8" dia., bears N.36½°W., 31 lks. dist. mkd. T30S R4W S33 BT.

A Fir 10" dia., bears S.56°E., 17 lks. dist. mkd. T30S R4W CC S33 and 34 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Oct. 13, 1959 - C.S. File 42/356-17

At Corner point, Set 1/2" x 1/2" x 30" Angle iron, from which 12" Alder bears East, 7.0 ft. mkd. S34 BT.

8" Fir bears N.36°E., 26.0 ft. mkd. S34 BT.

10" Laurel bears N.2°W., 33.6 ft. mkd. S33 T30S R4W BT.

I set this corner by intersection of a line East from Sec. Cor 3 & 4 (235.0') and south (317.0') from ¼ cor. 33/34 the dist. I show are approx. (Sketch on back of renewal) added 5/15/2024

Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-19H & M132-37

Found - ½"x½"x30" angle iron, from which 14" D.Fir BT, now a blow down stump with a tin cap, bears N.36°E., 26.0 ft.

18" Madrone (Laurel) BT, scribes not visible, bears N.2°W. 33.6 ft. I rescribe bark "T30S R4W S34 BT"

6 ft. steel fence post bears East. 0.5 ft.

Set - 3/4"x40" iron rod, with a 2½" alum. cap, over the angle iron, mkd: ROSEBURG RESOURCES CO.

C C

S 33 | S 34

RLS 430 2000

26" D.Fir BT, I scribed "T30S R4W S33 BT" bears N.75°W., 30.4 ft.

No BTs available in Sec. 34.