

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7112)

Set a stone 18x12x3 ins., 13" in the ground, for cor. to secs. 27, 28, 33 and 34, marked with three notches on E. and 1 notch on S. edges, from which

A Fir 10" dia., bears N.38°E., 13½ lks. dist. mkd. T30S R4W S27 BT.

A Fir 26" dia., bears S.75½°E., 45½ lks. dist. mkd. T30S R4W S34 BT.

A Fir 34" dia., bears S.85°W., 67¼ lks. dist. mkd. T30S R4W S33 BT.

A Fir 14" dia., bears N.26¼°W., 37¼ lks. dist. mkd. T30S R4W S28 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - June 29, 1960 - C.S. File 42/356-20

Determined by O.B.T.s:

16" dead Fir snag N.38°E., 8.9 ft., found scribe.

40" Fir S.75°E., 29.7 ft.

40" dead Fir S.85°W., 44.0 ft.

20" Fir stump, logged, N.26°W., 24.4 ft.

At corner point, Set wood post, from which

60" Fir bears S.52°W., 40.0 ft. mkd. S33 T30S BT.

50" Fir bears N.31°W., 107.0 ft. mkd. S25 T30S R4W BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - July 1963 - C.S. File 53/26-74

Found - All BTs as recorded by Markham, except SW. and SE. are now stumps. SW. now snag.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 4 W

S 28 | S 27

S 33 | S 34

1963

New BTs -4" Laurel bears S.24°E., 39.0 ft. scribed S34 CS BT T30S R4W.

4" Laurel bears N.(?)°W., 29.0 ft. scribed S28 CS BT. (No brg. given in C.S. File field notes)

No trees near to SW. or NE.

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1907, surveyed July 1999/Aug. 1999. (DCSO rec. Vol. 53 page(s) 20653-4)

The cor. of secs. 27, 28, 33, & 34, perpetuated by Markham, in 1960, further perpetuated by Byron, in 1963; monumented with an iron pipe, 1½" diam., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of original bearing trees
A decayed fir stump, 12" dia., bears N.38°E., 8.9 ft., with no marks visible.
A sawed fir stump, 27" dia., bears S.75½°E., 30.0 ft., with a healed blaze.
A sawed fir stump, 20" dia., bears N.23°W., 24.6 ft., with scribe marks 8 BT visible on partially opened blaze. (Record, N.26¼°W.)
and the remains of a bearing tree mkd. by Markham
A sawed fir stump, 56" dia., bears S.50½°W., 39.5 ft., with no marks visible.
and the bearing trees mkd. by Byron
A madrone, 12" dia., bears S.26¼°E., 39.5 ft., with a healed double blaze.
A madrone, 18" dia., bears N.82¼°W., 29.5 ft., with a healed double blaze.
and a new bearing tree
A fir, 5" dia., bears S.63°W., 22.9 ft., mkd. X BT.
No suitable accessories available in the NE. quadrant.
Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

Fd. Ok Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-19J & K and M132-37

Fd. ok by R. Rice, 7/2004 - M 145-20

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23839-40)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1¼" dia. firmly set, projecting 13" above ground, with a brass cap (properly) mkd from which the remains of the original BTs reported by Moore and Browning in 1999
A decayed fir stump, size indeterminate, bears N.38°E., 8.9 ft., no marks visible. Continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 30" dia., bears S.75½°E., 30.0 ft., with no marks visible on open blaze.
A hollowed, decayed fir stump, 23" dia., bears N.23°W., 24.6 ft., no marks visible.
and the remains of the BTs mkd. by Markham Jr., reported by Moore and Browning in 1999
A decayed fir stump, 56" dia., bears S.50½°W., 39.5 ft., no marks visible.
A decayed fir stump, 60" dia., bears N.32¾°W., 109.4 ft., with axe marks visible.
and the BTs mkd by Byron, reported by Moore & Browning in 1999
A madrone, 16" dia., bears S.26¼°E., 39.5 ft., with a healed blaze.
A madrone, 22" dia., bears N.82¼°W., 29.5 ft., with a healed blaze.
and a BT mkd. by Moore in 1999
A fir, 11" dia., bears S.63°W., 22.9 ft., with a healed double blaze.
and a new BT
A madrone, 7" dia., bears N.67¼°E., 17.3 ft., mkd. T30S R4W S27 BT in the bark
NAD 1983 (2011)
Latitude: 42°55'33.77" N. Longitude: 123°10'09.39" W.