

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6998)

Set 1/4 sec. post, from which
A Pine 48" dia., bears N.70°W., 230 lks. dist.
A Balm 15" dia., bears S.20°E., 250 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7058-59)

The old post is gone; the bearing tree in sec.22 also, but the stump of a Pine, corresponding in size 48" and direction, NW. to the description given in the field notes, stands. Mr. Pool, a long resident of this locality, informs me that this is the original bearing tree. I restore this cor. by setting a basalt stone, 20x8x8 ins., in a mound of stone, marked 1/4 on W. face, from which
A Maple 30" dia., bears S.20°E., 260 lks. dist. mkd. 1/4 S
BT
A Balm 24" dia., bears S.33 1/2°W., 248 lks. dist. mkd. 1/4 S
BT.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20101)

The witness corner for the 1/4 sec. cor. of secs. 21 and 22, established by Ware, in 1981, and is accepted; monumented with an iron rod, 5/8" diam., firmly set 4" below ground.
At the corner point
Set a stainless steel post, 28" long, 2 1/2" diam., 25" in the ground, with brass cap mkd.

W C
T30S R4W
1/4
S 21 | S 22
1993

from which
A cedar, 38" diam., bears South, 127 lks., mkd. X BT.
A maple, 7" diam., bears S.59°W., 231 lks., mkd. X BT.
Deposit a white "DEEP-1" magnetic marker at base of and iron rod alongside of stainless steel post.