

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6998)

-
- Set post cor. of secs. 15, 16, 21 and 22, from which
- A B.Oak 8" dia., bears N.30°W., 122 lks. dist.
 - A B.Oak 6" dia., bears N.7°E., 55 lks. dist.
 - A B.Oak 15" dia., bears S.75°W., 90 lks. dist.
 - A W.Oak 5" dia., bears S.30°E., 18 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7057-58)

-
- The post set for this corner is gone, but 3 of the original bearing trees in secs. 15, 21 and 22, corresponding to the description given in the field notes, are standing. I restore this cor. by setting a Fir post, 4 ft. long, 4' sq., 24" in the ground, marked T30S S15 on NE.; R4W S22 on SE.; S21 on SW.; S16 on NW. faces, with 3 notches on S. and E. edges, from which
- A B.Oak 14" dia., bears N.42½°E., 60 lks. dist. mkd. T30S R4W S15 BT.
 - A W.Oak 10" dia., bears S.30°E., 18 lks. dist. mkd. T30S R4W S22 BT.
 - A B.Oak 27" dia., bears S.74°W., 87 lks. dist. mkd. T30S R4W S21 BT.
- (These are the old bearing trees, which I re-mark as the old marks are dim.)
- A B.Oak 12" dia., bears N.10°W., 53 lks dist. mkd. T30S R4W S16 BT.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.e. Richardson, R.L. Irving - Feb. 26, 1940 - C.S. File 16/55; C.S. File 53/96

-
- Location identified from an original BT, an Oak snag N.10°W., 35 ft., scribe marks visible.
- Drove an iron pipe for corner from which
- A W.Oak 14" dia., bears N.34°50'W., 227.5 ft. mkd. T30S R4W S16 CS BT.
 - A Fir 42" dia., bears N.33°50'E., 218.5 ft. marked T30S R4W S15 CS BT.
 - A Fir 28" dia., bears S.67 3/4°E., 139.6 ft. marked T30S R4W S22 CS BT.
 - A W.Oak 16" dia., bears S.76°11'W., 317.9 ft. marked T30S R4W S21 CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

- A fir, 16" diam., bears N.33°E., 20½ lks., mkd. T30S R4W S15 BT.
- A fir, 18" diam., bears S.59¼°E., 31 lks., mkd. T30S R4W S22 BT.
- A fir, 21" diam., bears S.82¼°W., 25½ lks., mkd. T30S R4W S21 BT.
- A fir, 11" diam., bears N.71 3/4°W., 32½ lks., mkd. T30S R4W S16 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/26/2002 - C.S. File 66/32-16

-
- Found - 1959 DCSO brass cap iron pipe bent, protrudes 10" above ground.
1940 1½" I.D. iron pipe bent protrudes 10" above ground along easterly edge of BC/IP.
See 1959 BLM renewal for info on old BTs.
16" now 20" dia., 1½ ft. high D.Fir stump with a portion of healed blaze, bears N.33°E., 13.5 ft. (1995)
18" now 20" dia., 1½ ft. high D.Fir stump with a portion of healed blaze, bears S.59½°E., 20.5 ft. (1995)
21" now 24" dia D.Fir with a fully healed single blaze, bears S.82½°W., 16.8 ft. (1995)
11" now 12" dia., D.Fir with a fully healed single blaze, bears N.71¾°W., 21.4 ft. (1995)
- New - 9" dia., I.Cedar double blazed & scribed "T30S R4W S21 CS BT" bears S.6½°W., 25.2 ft.
11" dia., D.Fir double blazed & scribed "T30S R4W S15 CS BT" bears N.83½°E., 9.5 ft.
Both monuments removed & straightened. 1959 BC/IP set at plumb position, protrudes 3" above ground.
1940 IP set along north edge of BC/IP protrudes 1" out of ground.
Compass decl. 17½°E.

Fd. Ok by R. Brown, 2/2002 - M 137-36
FD. By D Edwards 12/2020 - 2020-0051