

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION W.C. for 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6998)

Set ¼ sec. post, from which
An Ash 4" dia., bears S.60°E., 30 lks. dist.
A W.oak 6" dia., bears S.45°W., 144 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7062)

Set a basalt stone 20x16x6 ins. in mound of stone, upon bed rock for witness corner to ¼ sec. cor. mkd. ¼ W C on W. face, 380 lks. S. of true cor. in the river, from which
A Pine 24" dia., bears West, 9 lks. dist. mkd. ¼ S WC BT
A B.Oak 12" dia., bears S.58½°E., 43 lks. dist. mkd. ¼ S WC BT.
The old corner and bearing trees are washed away.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; R.L. Irving - Feb. 26, 1940 - C.S. File 16/55

Set a stone 18" x 12" x 5" marked W.C. ¼ on top. Set from original BT in excellent shape.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - June 1963 - C.S. File 53/26-71

Found - Large Pine, West 5.9 ft., now down, shows scribing. SE. BT, not found.
Corner stone not found as it was in the uproot area.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 4 W
WC ¼ S16 | S15
1963
New BTs -9" W.Oak bears S.71°E., 16.8 ft. scribed ¼ S15 CS BT WC.
9" W.Oak bears S.11°W., 41.3 ft. scribed ¼ S16 CS BT WC.

Fd. OK June 1982 - M 92-18 A&B
Fd. OK April 1995 by R. Brown - M 119-62

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 29, 1998 - C.S. File 66/4-9

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 20" above ground, properly marked. 1963
(Cont. next page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1" I.D. iron pipe protrudes 9" above ground on North edge of BC/IP. Both I.P.s wired together. (Source unknown)

No evidence of BTs found.

Set - The iron pipes are surrounded by a mound of stone, brass cap protrudes 10" above mound.

5" dia., Ash double blazed and scribed "X BT" bears S.36½°W., 20.1 ft.

Multi trunked Ash, blazed and scribed "WC ¼ S15 CS BT" on 6" dia., southerly trunk center of southerly trunk bears S.76°E., 8.4 ft.

Double trunked Maple blazed and scribed "WC ¼ S15 CS BT" on 10" dia. Northerly trunk, center of root crown, bears S.8°E., 26.7 ft.

3" dia., W.Oak, double blazed and scribed "X BT" bears N.39°E., 12.1 ft.

Fd. Ok by R. Brown, 2/2002 - M 137-36