

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6999)

Set post cor. of secs. 3, 4, 9 and 10, from which
A B.Oak 10" dia., bears S.10°E., 25 lks. dist.
A B.Oak 8" dia., bears S.45°W., 28 lks. dist.
A B.Oak 15" dia., bears N.83°W., 55 lks. dist.
A B.Oak 6" dia., bears N.35°E., 19 lks. dist.
George Day's house, S.45°E.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7064)

The post set for this corner originally is gone, but I find another post in place, but all the bearing trees in Secs. 3 and 4 are standing and easily identified, also the stump of an Oak in Sec. 9, corresponding in size and direction with the one in this section described in the field notes furnished me. I replace the old and partially rotten post, by a Laurel post, 4 ft. long, 4" sq., 24" in the ground, marked T30S R4W S3 on NE.; R4W S10 on SE.; S9 on SW.; S4 on NW.; faces with 5 notches on S. and 3 notches on E. edges, from which
A B.Oak 12" dia., bears N.35°E., 19 lks. dist. mkd. T30S R4W S3 BT.
A B.Oak 27" dia., bears N.83°W., 55 lks. dist. mkd. T30S R4W S4 BT.
A Laurel 8" dia., bears S.34½°E., 29 lks. dist. mkd. T30S R4W S10 BT.
A Laurel 5" dia., bears S.61 3/4°W., 11 lks. dist. mkd. T30S R4W S9 BT.
The first two are old bearing trees, whose dim old marks I replace by marking anew. The last two are additional bearing trees to cor. of secs. 3, 4, 9 and 10, in place of the old destroyed bearing trees of original survey.

G.G. Stewart, Deputy Co. Surveyor - Wit: H.A. Hill; W.S. Crear - April 6, 1922 - C.S. File 7/6; Field book 3 Pg. 12

Reset from two Original BTs. Set Iron pipe. Marked:
An 18" B.Oak N.35°E., 12.5 ft.
A 24" B.Oak N.82°W., 36.6 ft.
A 22" B.Oak S.7½°E., 130.8 ft.
No other trees suitable.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Aug. 1963 - C.S. File 53/26-86

Found - 3/4" I.P., 3" under. We raise to 6" above, at corner.
Three BTs as recorded by Stewart.
New BTs -7" Laurel bears S.28°E., 13.5 ft. scribed S10 T30S R4W CS BT.
6" Laurel bears S.83°W., 17.0 ft. scribed S9 CS BT.

Fd. OK, June 1970 by L. Bishop - M 42-1

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16818)

The Sec. cor., perpetuated and recorded by Stewart, 1922, and further perpetuated and recorded by Byron in 1963, monumented with an iron pipe, 1/2" dia., firmly set, projecting 12" above ground, from which the remaining original bearing trees:
A B.Oak 20" dia., bears N.32½°E., 19 lks. dist., with healed double blaze. (Rec. N.35°E.)
A B.Oak 36" dia., bears N.83°W., 59 lks. dist., with healed blaze. (Rec. 55 lks.)
and bearing trees mkd. by Byron:
A Madrone 12" dia., bears S.32°E., 21 lks. dist. with fragmentary scribe marks visible on open blaze.
A Madrone 10" dia., bears S.82°W., 26 lks. dist. with scribe marks W S9 CS BT visible on open blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 30 S R 4 W
 S 4 | S 3
 S 9 | S 10
 1981
from which new bearing trees:
A Fir 6" dia., bears S.52½°W., 71½ lks. dist. mkd. T30S R4W S9 BT.
A Fir 8" dia., bears N.57°W., 57 lks. dist. mkd. T30S R4W S4 BT.
Reset iron pipe alongside iron post.

Fd. ok, BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20103)