

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7000)

-----  
Set ¼ sec. post at proper distance, from which  
An Alder 8' dia., bears N.45°W., 26 lks. dist.  
A W.oak 20" dia., bears S.8°E., 45 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7067)

-----  
The post for this corner is gone. I find a B.Oak marked ¼ S BT. Taking this to be called an Alder in the field notes of original survey, (no other bearing trees could be found, and no Alders anywhere,) I restored this corner by setting a Laurel post 3 ft. long, 3" sq., 24" in the ground, marked ¼ S on W. face, from which  
A B.Oak 24" dia., bears S.45°W., 26 lks. dist. mkd. ¼ S BT. This had been marked, but I renew the marks, the same being dim.  
A W.Oak 6" dia., bears N.34½°E., 83 lks. dist. mkd. ¼ S BT

G.G. Stewart, Deputy Co. Surveyor - Wit: H.A. Hill; W.S. Crear; - April 6, 1922 - C.S. File 7/6; Field book 3 Pg. 12

-----  
I set an Iron pipe for corner from original BT, which was a 24" B.Oak instead of W.Oak as called for. Bearing did not check. Marked:  
A 24" B.Oak S.32°W., 30.0 ft. (OBT)  
An 18" Pine tree, S.42°E., 23.5 ft.

Survey by Frederick E. Warner - For: J.H. Baxter & Co. - March/April 1957 - C.S. File 42/257

-----  
I find Iron pipe, 1/2" dia., 4" above ground, unmarked. Set an Iron pipe over corner, 1½" dia., 36" long, 28" in ground, and mark RS 298, from which  
A B.Oak 24" dia., bears S.37°W., 17.16 ft., down and mkd. ¼ S BT.  
A W.oak 6" dia., bears N.35°E., 54.78 ft., down and decayed with partial scribe marks.  
New BTs -  
A D.Fir 28" dia., bears S.78°E., 22.44 ft. mkd. ¼ S3 RS 298 BT.  
A Cedar 26" dia., bears N.76°W., 36.96 ft. mkd. ¼ S4 RS 298 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Marvin C. Ramsey - For: J.H. Baxter & Co. - Wit: R.Burch and J. Beed - May 6, 1959 - C.S. File 51/19; C.S. File 7/6

-----

Monumented with an Iron pipe 3 ft. long, 1½" dia., 8" above ground and mkd. RS 298, from which

A D.Fir 28" dia., bears S.78°E., 34 lks. mkd. ¼ S3 RS298 BT.

A Cedar 26" dia., bears N.76°W., 56 lks. dist. mkd. ¼ S4 RS298 BT.

Fd. OK, June 1970 - By L.Bishop - M 42-1

Ron Quimby - For: Roseburg Forest Products - March 1996 - M 123-58

-----

Found - 1½" iron pipe at the corner from which a:

32" (28") D.Fir, bears S.78°E., 22.7', with scar.

27" (26") Cedar (now a stump), bears N.76°W., 37.4', with visible scribing.

17" Cedar, bears S.15.°W., 47.7', with visible scribing. (NO record of this BT)

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20104-5)

-----

The ¼ sec. cor. of secs. 3 & 4, perpetuated by Stewart, in 1922, further perpetuated by Warner in 1957, further perpetuated by Ramsey, in 1959; monumented with an iron pipe, 1½" diam., firmly set, projecting 8" above ground, from which the remains of an original bearing tree:

A root hole, bears S.35½°W., 26 lks., with decayed oak trunk, 24" diam., alongside, with no marks visible on decayed face. (Record, S.45°W.)

and the remains of bearing trees mkd. by Warner

A fir, 34" diam., bears S.77¼°E., 33 lks., with healed blaze.

A sawed cedar stump, 28" diam., bears N.76°W., 55 lks., with healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, directly over the iron pipe, with brass cap mkd.

T30S R4W

1/4

S 4 | S 3

1994

continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree  
A cedar, 17" diam., bears S.16½°W., 72 lks., mkd. ¼ S4 BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23512)

-----  
The ¼ sec. cor. bet secs. 3 & 4, monumented with a stainless steel post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree reported by Seibold and Browning in 1993-95

A root hole bears S.35½°W., 17.2 ft., with fallen, decayed oak trunk, 24" dia., lying alongside, with no marks visible.

and the remains of the bearing trees mkd. by Warner, in 1957, reported by Seibold and Browning

A fir, 35" dia., bears S.77¼°E., 21.8 ft., with a healed blaze.

A sawed cedar stump, 28" dia., bears N.76°W., 36.3 ft., with a healed blaze.

and the bearing tree mkd. by Seibold and Browning

A cedar, 19" dia., bears S.16½°W., 47.5 ft., with a healed blaze.

NAD 1983 (2011)

Latitude: 42°59'25.389"N. Longitude: 123°10'04.711"W