

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7068)

For Closing cor. of secs. 3 and 4, I set a Fir post, 4½ ft. long, 4" sq., 24" in the ground, marked CC T30S R4W on S. face, S3 on E. face, S4 on W. face, and 3 notches on E. and W. faces, from which
A Laurel 16" dia., bears S.65°E., 34 lks. dist. mkd. T30S R4W S3 BT.
A Fir 36" dia., bears S.8°W., 24 lks. dist. mkd. T30S R4W S4 BT.

John H. Markham, Jr. - For: Stomar Lbr. Co. Wit: Dennis & Geo. Vaughn - Nov. 2, 1951 - C.S. File 40/386-4

I could read scribe on both old BTs and rescribed them.
At corner point, SET 1" x 30" I.P., from which
A Fir 9" dia., bears S.46°E., 27.5 ft. mkd. S3 BT.
A Cedar 15" dia., bears S.6°E., 310 ft. mkd. S3 BT.
A Laurel 17" bears S.65°E., 22.0 ft. (Orig. BT)
A Fir 48" bears S.8°W., 16.0 ft. (Orig. BT)

Marvin C. Ramsey - For: J.H. Baxter & Co. - Wit: R. Burch and J. Beed - Filed May 6, 1959 - C.S. File 51/19

Monumented with an Iron pipe 1¼" dia., 3" below surface of the ground and marked RS298, from which
A Cedar 20" dia., bears S.5°E., 48 lks. dist. mkd. S3 BT.
A D.Fir 48" dia., bears S.10°W., 27 lks. dist. mkd. S4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-136

Found - 1" I.P. at corner.
20" Cedar S.5°E., 31.0 ft. scribing visible.
SW BT, now stump.
New BT - 8" R.Fir bears S.56°W., 51.3 ft. scribed S4 T30S R4W CS BT.

Fd. Ok by Ron Quimby, March 1996 - M 123-58


BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20106-7)

True point for the closing cor. of secs. 3 and 4.
continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.



from which

A fir, 17" diam., bears S.42¼°E., 53 lks., mkd. T30S R4W S3 CC BT.

A fir, 18" diam., bears S.84½°W., 80 lks., mkd. T30S R4W S4 CC BT.

From this point, the original closing cor. of secs. 3 & 4, perpetuated by Markham, in 1951, further perpetuated by Ramsey, in 1959, further perpetuated by Byron, in 1963, bears N 0°19'57"W., 0.038 chs.; monumented with an iron pipe, 1¼" diam., firmly set, projecting 1" above ground, from which the remains of an original bearing tree:

A sawed fir stump, 36" diam., bears S.8°W., 27 lks., with no marks visible. (Record, 24 lks.)

and the remains of a bearing tree mkd. by Markham

A cedar, 27" diam., bears S.5°E., 48 lks., with healed double blazes.

and a bearing tree mkd. by Byron

A fir, 17" diam., bears S.55 3/4°W., 78 lks., with healed double blazes.

From this same point, the ¼ sec. cor. of sec. 34 only, T29S R4W bears S.88°52'15"E., 5.742 chs.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23511-12)

The closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., bears N.88°54'54"W., 379.30 ft., monumented with a stainless steel post, firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the BTs mkd. by Seibold and Browning in 1993-95

A fir, 21" dia., bears S.42¼°E., 35.0 ft., with a healed blaze.

A fir, 20" dia., bears S.84½°W., 52.8 ft., with a healed blaze.