

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6986)

- 
- Set a post at proper distance cor. of secs. 3, 4, 33 and 34, from which
- A Laurel 6" dia., bears S.75°W., 20 lks. dist.
  - A Laurel 6" dia., bears S.6°E., 80 lks. dist.
  - A Laurel 4" dia., bears N.45°E., 15 lks. dist.
  - A Red Fir 18" dia., bears N.45°W., 25 lks. dist.

*(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W., on the offset Meridian Line, - - - -" (V. Laugen, March 1996)*

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7019-20)

- 
- A Fir, 12" dia., is cor. to secs. 33, 34, 3 and 4, marked T30S S34 on NE.; R4W S3 on SE.; T31S S4 on SW.; S33 on NW. faces with 3 notches on E. and W. edges, from which
- A Fir 33" dia., bears N.55½°E., 64 lks. dist. mkd. T30S R4W S34 BT.
  - A Fir 30" dia., bears S.76°E., 59 lks. dist. mkd. T31S R4W S3 BT.
  - A Fir 16" dia., bears S.52°W., 12 lks. dist. mkd. T31S R4W S4 BT.
  - A Laurel 12" dia., bears N.42°W., 17 lks. dist. mkd. T30S R4W S33 BT.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Pgs. 7114-15 and Vol. 18 Pg. 7835)

-----

(Pg. 7114-15)  
Bushey tied and described Thiel's corner.  
(Pg. 7115)  
As this is not the corner to Secs. 33 and 34, I destroy the marks on the NE. and NW. faces of this corner and the mark on the witness trees North of this line in T30S R4W.  
(Pg. 7835)  
As the old cor. established for secs. 3, 4, 33 and 34, is not a cor. to secs. 3 and 4, I destroy the marks on the SE. and SW. faces and the marks on the E. and W. edges of the tree

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 406100

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

cor. and also the marks on the 2 Fir witness trees S. of the cor. in T31S R4W.

Survey by B. Shaner - Corner looked for and not found, July 2000 - See M132-37 and CS File 65/30-19L.

Jerry Estabrook - For: Roseburg Resources - 5/2003 - C.S. File 65/45-32M & M142-36

-----  
Found - Madrone 24" rotten sawed stump bears N.42°W. 12.5 ft  
Fir 31" sawed stump with "BT" visible scribe bears S.47°W., (S.52°W.) 7.9 ft. (I sawed into & split out at pitch seam)  
Fir shell remnant size indeterminate (estimated 40±") bears S.82°E., (S.76°E.), 40.0 (38.9) ft.  
Fir 47" sawed stump bears N.51°E., (N.55°30'E.) 43.3 (42.2) ft.

All distances measured to center.

Set - Fd. 30"x3 ft. tall stump, sawed into & split pitch seam. Fd. legible scribing on all 4 quadrants. Cut off stump & bored vertical hole in heart. Set 5/8"x30" iron rod 28" deep in bored hole with 2½" alum. cap stamped

AP  
T30S R4W  
S 34  
S 3  
T 31 S  
2003  
LS 2703

New BOs- 1½" alum. cap stamped on 5/8"x30" iron rod set 28" deep bears N.8°E., 6.0 ft. B O  
1  
LS 2703

1½" alum. cap stamped on 5/8"x30" iron rod set 28" deep bears S.30°E., 7.0 ft. B O  
2  
LS 2703

Light weight steel fence/guard post set new bearing BO 1 & BO 2.