

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 7000)

-----  
Set ¼ sec. post at average distance, from which  
A B.Oak 14" dia., bears S.85°W., 400 lks. dist.  
A W.Oak 6" dia., bears N.32°W., 77 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7066)

-----  
The old post is gone, both bearing trees are standing. I restore this corner by setting a Cedar post, 3 ft. long, 3" sq., 24" in the ground, marked ¼ S on N. face, from which  
A W.oak 14" dia., bears N.32°W., 77 lks. dist. mkd. ¼ S BT. This is the old bearing tree, whose marks I renew.  
A B.Oak 4' dia., bears S.87½°W., 150 lks. dist. mkd. ¼ S BT.

F.C. Frear, Deputy Co. Surveyor - Wit: C.J. Wilson; E.N. Armiston - Nov. 21, 1918 - Vol. 3 Pg. 34

-----  
Set from old BTs. Set in an 8" x 12" x 18" boulder, from which  
A 20" W.Oak bears N.32°W., 77 lks. dist.  
A 10" B.Oak bears N.76°W., 84 lks. dist.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Aug. 14-18, 1957 - C.S. File 42/288-10

-----  
As determined by old BTs found:  
20" W.Oak bears N.33°W., 50.8 ft.  
12" B.Oak bears N.79°W., 55.5 ft. found scribing.  
At corner point, Set 1" x 30" Iron rod 26" in ground, from which  
15" Laurel bears N.42°W., 86.7 ft. mkd. ¼ S3 T30S R4W BT  
8" W.Oak bears N.38°E., 81.0 ft. mkd. ¼ S3 R4W BT.  
A fence running East and West bears North, 37.0 ft.  
Corner lies on North edge of large field.

Fd. OK, June 1970 - M 42-1

Douglas Co. Surveyor Office - R.B. Kimberling; M.W. Cline - Oct. 6, 1977 - C.S. File 59/40-35

-----  
Found - 1" Iron rod 6" above ground and bent over.  
6" now 16" W.Oak bears N.32°W., 50.8 ft. with rotted out blaze and Stomar Lbr. Co. tag. (OBT use to set brass cap) (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A 14" B.Oak bears N.79°W., 55.5 ft. with well healed double blaze.  
A 15" Madrone bears N.42°W., 87.6 ft. (Rec. 86.7 ft. good to face) Tree is triple trunked, measured to South fork with visible scribing on almost healed single blaze.  
An 8" now 10" W.Oak bears N.38°E., 81.0 ft. with a well healed double blaze.  
Set a 1" x 36" I.P. with brass cap 5" above ground, marked:  
Douglas County Surveyor  
T 30 S R 4 W  
1/4  
S 3  
S 10  
1977  
Set a steel fence post 7" SE. of brass cap and a wooden lath with flagging 1.0 ft NW & a 14"x8"x10" boulder at West side. An E-W fence bears North 38 ft. Corner is on N. edge of cultivated field.

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group # 1070, surveyed June 1981/ May 1982 - (DCSO records, Vol. 43 Page 16817)

Fd Ok by Ron Quimby, March 1996 - M 123-58

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23517)

-----  
The ¼ sec. cor. of secs 3 & 10, monumented with an iron post, 1¼" dia., firmly set, projecting 3" above ground (alongside of which is a mound of stone, 2 ft. base, 1 ft. high, N. of the iron post), with brass cap (properly) mkd. from which the remaining original bearing tree reported by Jelley in 1981-82  
An oak, 20" dia., bears N.35°W., 50.8 ft., with no marks visible on an open blaze.  
and the remains of the BTs mkd. by Markham, in 1951, reported by Jelley  
A W.Oak snag, 11" dia., bears N.35°E., 81.2 ft., with no marks visible on an open blaze.  
A madrone, 16" dia., bears N.42°W., 86.5 ft., with a healed double blaze.  
and a new bearing tree  
A fir, 7" dia., bears N.53¾°E., 33.4 ft., mkd. ¼ S3 BT.  
NAD 1983 (2011) Lat: 42°58'59.816"N Long: 123°09'29.684"W