

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Aug/ 1957 - C.S. File 42/288-11

At a point where N-S and E-W cross, I set a 3/4" x 30" iron pipe, from which
31" Laurel bears S.41°E., 34.7 ft. mkd. ¼ S3 C.C. T30S R4W BT.
33" Laurel bears N.83°E., 48.0 ft. mkd. ¼ S3 C.C. T30S R4W BT.
¼ corner bears West, 2612 ft.
¼ corner bears East 2660 ft.

Fd. OK, June 1970 by L. Bishop - M 42-1

Douglas County Surveyors Office - R.B. Kimberling, Deputy - M.W. Cline, crew - Oct. 1977 - C.S. File 59/40-40

Found - A 3/4" Iron pipe 22" in ground.
31" Madrone bears S.35°E., 34.2 ft. (Rec. S.41°E., 34.7 ft.) with visible scribing in an almost healed double blaze.
33" Madrone bears N.87½°E., 46.6 ft. (Rec. N.83°E., 48.0 ft.) with visible scribing " /4 S3 T30S R4W" in partially healed double blaze.
Set 1" x 30" Iron pipe with brass cap 6" above ground marked:
Douglas County Surveyor
T 30 S R 4 W
S 3
C 1/4
1977

No new accessories.

Ron Quimby - For: Roseburg Forest Products - March 1996 - M 123-58

Set - 5/8" x 30" iron rod with plastic cap marked: "AA SURVEYING, INC." at the corner from which a:
1" iron pipe with DCSO brass cap, bears S.61°50'W., 8.92', w/bearing trees per DCSO 1977 corner renewal.
New?- 12" D.Fir, bears N.51°E., 63.1', marked: "C¼ S3 BT".
13" R.Fir, bears N.25°E., 28.6', marked: "C¼ S3 BT".
15" Cedar, bears Due West, 81.1', marked: "C¼ S3 BT".
15" D.Fir, bears N.80°W., 65.5', marked: "C¼ S3 BT".

continued next page

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23517-8)

The center ¼ sec. cor. of sec. 3, established by Quimby, in 1996, and is accepted as the cor., monumented with an iron rod, 30" long, 5/8" dia., firmly set, projecting 4" above ground, with yellow plastic cap mkd. AA SURVEYING INC, from which the remains of bearing trees mkd by Quimby

A root hole bears N.10½°E., 26.3 ft., with fallen fir trunk, 13" dia., lying alongside, with a healed blaze.

A fir, 16" dia., bears N.27¼°E., 28.0 ft., with scribe marks C¼ S3 BT visible on a partially healed blaze.

A cedar, 22" dia., bears N.86½°W., 81.5 ft., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 21" dia., bears N.76¾°W., 65.3 ft., with fragmentary scribe marks visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T 30 S R 4 W

C ¼ S 3

2015

From this cor., a point erroneously established as the center ¼ sec. cor. of sec. 3 by Markham, in 1957, accepted and utilized by Bishop, in 1970, and perpetuated by the Douglas County Surveyor's Office in 1977 bears S.61°32'04"E. 9.06 ft, and is not utilized in the course of this survey, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap mkd. DOUGLAS COUNTY SURVEYOR T30S R4W S3 C¼ 1977 (alongside of which is an iron post, 1" dia., firmly set, projecting 5" above ground), from which the remains of bearing trees mkd. by Markham, Jr.

A decayed madrone snag, 22" dia., bears N.85¼°E., 45.1 ft., with no marks visible.

A madrone, 32" dia., bears S.36½°E., 33.5 ft., with no marks visible on an open blaze.

The 1978 BLM Administrative survey monument, an iron pipe, 30" long, 1" dia., was found lying loose on the ground surface and determined to have been disturbed from its original position. Bury the iron pipe alongside the stainless steel post.