

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCS0 records Vol. 17 Page(s) 7109)

A Maple 4" dia., which I mark 1/4 S on W. face, for 1/4 sec. cor., from which

A Fir 8" dia., bears S.88 1/2°E., 39 lks. dist. mkd. 1/4 S BT.

A Laurel 6" dia., bears N.58 3/4°W., 32 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Feb. 1959 - C.S. File 42/356-6

At the proportional distance, I Set 3/4" x 30" Iron rod for 1/4 corner, from which

12" Fir bears S.42°E., 24.0 ft. mkd. 1/4 S35 BT.

12" Fir bears S.74°W., 21.0 ft. mkd. 1/4 S34 BT.

7" Laurel bears N.43°W., 13.6 ft. mkd. 1/4 S34 BT.

NE Corner 34 bears North, 2600.0 ft.

SE Corner 34 bears South, 253.0 ft.

Douglas County Surveyors Office - M. Lenora Ladig; Peter L. Earle, crew - June 10, 1976 - C.S. File 59/15-16

Found - 1" x 30" I.Pipe (Rec. calls for 3/4" x 30" iron rod)

12" now 16" Fir bears S.42°E., 24.0 ft. Tree alive with "35" visible in pitched over scar.

12" now 22" Fir bears S.74°W., 21.0 ft. Tree alive with well healed blaze.

7" now 9" Laurel bears N.43°W., 13.6 ft. Tree is alive with "1/4 S34 BT" visible bark scribe.

At true corner point, Set a 1" x 36" I.Pipe with brass cap stamped: Douglas County Surveyor

T 30 S R 4 W

S 34 S 35

1/4

1976

Placed 1" I.P. on North side of cap.

Did not mark new trees.

To reach corner, go approx. 1000 ft. West of Rd. #30-4-22.0 to SE. Cor. Sec. 34, than North 253.0 ft. to 1/4 cor. which lies in N-S cutting line.

Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-19S & M 132-37

Found - 2 1/2" brass cap on a 1"x30" iron pipe from which

24" D.Fir BT face overgrown, bears S.79°W., 18.5 ft. (rec. S.74°W., 21.0 ft.) continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	12" Madrona (Laurel) BT scribes visible, bears N.43°W., 13.6 ft. 16" D.Fir BT, bearing S.42°E., 24.0 ft., now gone. 1" iron pipe on North side of BC. 26" D.Fir BT, I scribed "¼ S35 BT" bears N.6°E., 10.8 ft. 6 ft. steel fence post, North 1.0 ft.
-------	---

Fd BC, 3 BTs & steel post by R. Rice 8/7/2012 - C.S. file 65/77-21
--

--