

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7016)

-----  
A Fir 20" dia., which I mark  $\frac{1}{4}$  S on W. face for  $\frac{1}{4}$  sec. cor., from which

A Fir 30" dia., bears N.47 $\frac{1}{2}$ °E., 14 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S BT

A Fir 24" dia., bears N. $\frac{1}{2}$ °W., 29 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S BT.

Survey by John H. Markham, Jr. - Wit: J.R. Markham - For; Stomar Lumber Co. - Aug. 5, 1960 - C.S. File 42/356-24

-----  
Determined by OBTs:

36" Fir stump, logged, bears N.47°E., 9.6 ft., found scribe.

26" Fir stump, logged, bears North 19.5 ft.

At Corner point found dead 22" Fir snag scribed on West face, and SET 3/4" x 40" I.P., from which

12" Laurel bears S.80°W., 39.0 ft. mkd.  $\frac{1}{4}$  S27 T30S R4W BT.

12" Chip bears S.43°W., 34.3 ft. mkd.  $\frac{1}{4}$  S27 BT.

12" Fir bears S.11°W., 21.7 ft. mkd.  $\frac{1}{4}$  S26 BT.

3" Fir bears S.50°E., 8.0 ft.  $\frac{1}{4}$  S BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1907, surveyed July 1999/Aug. 1999. (DCSO rec. Vol. 53 page(s) 20650-1)

-----  
The  $\frac{1}{4}$  sec. cor. of secs. 26 & 27, perpetuated by Markham, in 1960; monumented with the decayed remains of the original corner tree, a decayed fir stump, 19" dia., no marks visible, (with an iron pipe, 1" dia., firmly set, projecting 18" above ground, on NW. side of decayed stump), from which the remains of the original bearing trees:

A sawed and decayed fir stump, 38" dia., bears N.39 $\frac{1}{2}$ °E., 9.6 ft., with no mks. visible. (Record , N.47 $\frac{1}{2}$ °E.)

A sawed and decayed fir stump, 34" dia., bears N. $\frac{1}{2}$ °W., 19.5 ft., with no marks visible.

and bearing trees mkd. By Markham

A fir, 25" dia., bears S.15 $\frac{1}{4}$ °W., 19.9 ft., with a healed blaze.

A madrone, 19" dia., bears S.82 $\frac{3}{4}$ °W., 40.2 ft., with no marks visible.

At the corner point

Set a finned aluminum rod,  $\frac{3}{4}$ " dia., 36" long, 30" in the center of sawed, and decayed, corner tree, with 3". aluminum cap mkd.

continued next page

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 30 S R 4 W  
1/4  
S 27 | S 26  
1999

from which a new bearing tree  
A fir, 13" dia., bears S.84°E., 27.6 ft., mkd. ¼ S26 BT.  
Corner is located in a ravine, drains N.65°W.

Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail)  
driven at the base on right side-center, unless otherwise  
described in the corner description.

---

Fd. Ok by Kristian DeGroot - 11/2006 - M146-49

---