

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6993-94)

-
- Set post, corner of secs. 22, 23, 26 and 27.
- A Red Fir 16" dia., bears N.60°E., 24 lks. dist.
 - A Red Fir 16" dia., bears N.38°W., 10 lks. dist.
 - A Red Fir 18" dia., bears S.50°E., 37 lks. dist.
 - A Red Fir 8" dia., bears S.40°W., 25 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7041 and 7042)

I went to the locus of the cor. of secs. 22, 23, 26 and 27, but could not find any trace of a post or bearing trees. W.H. Graham, who lives in Sec. 22 and who accompanied me up here on my search for this cor., informs me that he has repeatedly and thoroughly searched for cor. witness tree, or blazes on this line, also for blazes on lines E. and W. of here, but without success.

Set a Cedar post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 22, 23, 26 and 27, marked T30S S23 on NE.; R4W S26 on SE.; S27 on SW.; S22 on NW. faces, with 2 notches on S. and E. edges, from which

- A Fir 36" dia., bears N.24°E., 26 lks. dist. mkd. T30S R4W S23 BT.
- A Fir 24" dia., bears S.1°E., 102 lks. dist. mkd. T30S R4W S26 BT.
- A Fir 30" dia., bears S.79°W., 44 lks. dist. mkd. T30S R4W S27 BT.
- A Fir 36" dia., bears N.29°W., 76 lks. dist. mkd. T30S R4W S22 BT.

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7105-06)

At the sec. cor., which is a post, 4" sq., firmly set, mkd. T30S S23 on NE.; R4W S26 on SE.; S27 on SW.; and S22 on NW. faces, with 2 notches on E. and S. edges, from which

- A Fir 36" dia., bears N.24°E., 26 lks. dist. mkd. T30S R4W S23 BT.
- A Fir 24" dia., bears S.1°E., 102 lks. dist. mkd. T30S R4W S26 BT.
- A Fir 30" dia., bears S.79°W., 44 lks. dist. mkd. T30S R4W S27 BT.
- A Fir 36" dia., bears N.29°W., 76 lks. dist. mkd. T30S R4W S22 BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

These trees are all marked in the bark, and the marks are getting dim. I mark them in the wood as follows:

- A Fir 36" dia., bears N.24°E., 26 lks. dist. mkd. T30S R4W S23 BT.
- A Fir 24" dia., bears S.1°E., 102 lks. dist. mkd. T30S R4W S26 BT.
- A Fir 30" dia., bears S.79°W., 44 lks. dist. mkd. T30S R4W S27 BT.
- A Fir 36" dia., bears N.29°W., 76 lks. dist. mkd. T30S R4W S22 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Nov. 10, 1958 - C.S. File 42/356-4

Determined by O.B.Ts
42" Fir N.24°E., 17.2 ft. (OBT)
24" Fir, logged stump, bears S.1°E., 69.0 ft. (OBT) found scribe.
42" Fir S.79°W., 30.5 ft. (OBT)
36" Fir N.29°W., 53.0 ft. (OBT)
At corner point, found stone and SET 2" x 40" steel shaft, from which
16" Laurel bears S.82°E., 26.0 ft. mkd. S 26 BT.
14" Laurel bears N.30°E., 8.5 ft. mkd. S23 BT.
10" Laurel bears N.29°W., 39.4 ft. mkd. S22 T30S BT.
14" Fir bears N.58°W., 4.2 ft. mkd. S22 BT.
Top of ridge bears West, 120.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - June 1963 - C.S. File 53/26-64

Found 2" steel shaft at corner and bearing trees as follows:
14" Laurel N.30°E., 8.5 ft., OK, shows scribing.
16" Laurel S.82°E., 26.0 ft. Road took out tree.
10" Laurel N.29°W., 39.4 ft., now stump, BT showing.
14" Fir N.58°W., 4.2 ft., down, good scar.
New BTs
8" Laurel N.18°W., 33.0 ft. scribed T30S R4W S22 CS BT.
6" Laurel S.85°W., 21.8 ft. scribed T30S R4W S27 CS BT.
Road bears East, 24.0 ft.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCS0 records Vol. 43 Page(s) 16810-11)

The sec. cor., perpetuated and recorded by Markham in 1958, and further perpetuated and recorded by Byron in 1963,
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

monumented with an axle 2½" dia., firmly set, protruding 14" above ground, from which the remains of bearing trees mkd. by Thiel:

A sawed Fir stump 30" dia., bears N.24°E., 26 lks. dist., with healed blaze.

A Fir 45" dia., bears S.79°W., 44 lks. dist. with healed blaze.

A sawed Fir stump 30" dia., bears N.29°W., 76 lks. dist. with healed blaze.

and the remains of bearing trees mkd. by Markham:

A sawed Madrone stump 13" dia., bears N.28°E., 13 lks. dist. no marks visible.

A root hole bears N.58°W., 6½ lks. dist. with a down Fir alongside, 16" dia., with healed double blaze.

A decayed Madrone stump, size indeterminate, bears N.29°W., 58 lks. dist., with scribe marks BT visible on decayed blaze.

and bearing trees mkd. by Byron:

A Madrone 10" dia., bears S.83°W., 31 lks. dist., with healed double blaze.

A Madrone 10" dia., bears N.20°W., 33 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 4 W	
S 22	S 23
S 27	S 26
1981	

from which new bearing trees:

A Fir 28" dia., bears N.52½°E., 221 lks. dist. mkd. T30S R4W S23 BT.

A Fir 9" dia., bears S.51°E., 84 lks. dist. mkd. T30S R4W S26 BT.

Reset axle alongside iron post.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1907, surveyed July 1999/Aug. 1999. (DCSO rec. Vol. 53 page(s) 20651-2)

 The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2½" diam., firmly set, projecting 6" above ground, with brass cap mkd.

T 30 S R 4 W	
S 22	S 23
S 27	S 26
1981	

from which the remains of bearing trees mkd. by Thiel
 continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A sawed and decayed fir stump, 27" dia., bears N.24°E., 17.2 ft., with a healed blaze.
A fir, 44" dia., bears S.79°W., 29.0 ft., with a healed blaze.
and the remains of bearing trees mkd. by Markham, in 1958
A sawed madrone stump, 16" dia., bears N.28°E., 8.6 ft., with no marks visible.
A roothole, bears N.58°W., 4.3 ft., with the rotted remains of fir alongside, size indeterminate.
A decayed madrone stump, size indeterminate, bears N.29°W., 38.3 ft., with no marks visible.
and remains of bearing trees mkd. by Byron, in 1963
A madrone, 10" dia., bears S.81¼°W., 21.0 ft., with no marks visible. (Record, S.83°W., 20.5 ft.)
A madrone snag, 8" dia., bears N.20°W., 21.8 ft., with no mks. visible.
and bearing trees mkd. by Jelley
A fir, 33" dia., bears N.52½°E., 145.9 ft., with a healed blaze.
A fir, 14" dia., bears S.50¼°E., 56.3 ft., with a healed blaze. (Record, S.51°E., 55.4 ft.)
and a new bearing tree
A cedar, 10" dia., bears N.2½°W., 11.7 ft., mkd. T30S R4W S22 BT.
Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.
Latitude 42°56'25.80"N
Longitude 123°09'00.17"W
(NAD 1927) (added 6/25/2008)
Corner is located W., 23.0 ft. of a graveled road, 20 ft. wide, bears N.30°E. and S.30°W.

From this point, U.S. Geological Survey triangulation station "BLAND MTN", bears N.38°24'36" E., 13304.59 ft., (mean bearing and sea level); monumented with a bronze disk, cemented flush in solid rock, with top mkd. "BLAND MTN 1953" and a triangle.

Ken Hoffine - For: Lone Rock Timberland Co. - Feb. 2017 - M173-10

Found - 1981 BLM BCIP
27" Fir stump bears N.23¾°E., 17.65 feet (record N.24°E., 17.2 ft) chopped out face and tag.
44" Fir bears S.80¼°W., 30.4 ft (rec S.79°W., 29.0 ft) healed face & tag madrone stump bears N.28½°E., 8.9 ft (rec N.28°E 8.6 ft) healed face and tag. CONT

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec Cor for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" madrone bears S.81½°W., 21.1 ft (record S.81¾°W., 21.0 ft) healed face and tag.
36" Fir bears N.52¾°E., 145.7 ft (record N.52½°E., 145.9 ft) healed face and tag.
17" Cedar bears N.3½°W., 11.9 ft (record N.2½°W., 11.7 ft) healed face and tag.
Large Fir stump bears N.30°W., 51.1 ft (record N.29°W., 50.16 ft) tag corner lies approx. 25 ft West of rock BLM Road 30-4-22.0, with a metal fence post approx. 0.5 feet north of corner.