

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6995-96)

Set ¼ sec. post, from which
A B.Oak 7" dia., bears S.35°W., 40 lks. dist.
A W.Oak 10" dia., bears N.80°E., 100 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7048)

The old post is gone; the W.Oak, 12" dia., mkd. ¼ S BT is standing, but the Oak in Sec. 15 is gone. I restore this cor. by setting an Oak post, 3 ft. long, 3" sq., 24" in the ground, mkd. ¼ S on W. face, from which
A W.Oak 12" dia., bears N.80°E., 100 lks. dist. mkd. ¼ S BT. (This is the old bearing tree which I re-mark, the old marks being dim.)
A B.Oak 8" dia., bears S.31°W., 47 lks. dist. mkd. ¼ S BT.

Survey by G.G. Stewart, Deputy Co. Surveyor - Subd. Sec. 15 -Dec. 29, 1922 - C.S. File 7/31; M 2-9; Vol. 3 Pg. 136

Marked by stake and rock mound, from which
18" B.Oak, N.56°W., 41.9 ft.
12" W.Oak N.80°E., 66.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - July 1963 - C.S. File 53/26-68

Found - Mound of stones and stake at corner.
18" B.Oak N.56°W., 41.9 ft. chopped into, found scribing.
12" W.Oak N.80°E., 66.0 ft. face rotted out, snag.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 4 W
S15|S14
1963
New BTs -20" Fir S.21°W., 36.0 ft. scribed ¼ S15 CS BT.
5" W.Oak N.36°E., 17.7 ft. scribed ¼ S14 CS BT.

Fd. OK, June 1982 by Wm. Ruppert - M 92-18 A&B