

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6996)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.83°W., 175 lks. dist.
A B.Oak 14" dia., bears N.58°E., 183 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7051-52)

A Post, marked ¼ S is standing here, but it is not the original one. I find no Oaks, answering the size, bearing, or distances described in the field notes furnished me. There are plenty of Oaks around here, all have been chopped into for the purpose of discovering any marks, but the County Surveyor informs me, without success. There must be some gross mistake in the field notes of original survey, for it places Days Creek 4.00 chs. North of this corner, while it is 27.00 chs. as the survey of Donation Land Claim No. 49 connects with this cor. I run from this cor. North 12.50 chs. to S. Bdy. of said Claim, thence West 16.00 chs. to its SW. cor., agreeing with the field notes of survey of said Claim, thus verifying its original position. This is also the accepted cor. by the settlers here.

I restore this cor. by replacing the partially decayed post by a W.Oak post, 3 ft. long, 4" sq., 24" in the ground, marked ¼ S on W. face, from which
A B.Oak 6" dia., bears S.77°E., 45 lks. dist. mkd. ¼ S BT
An Alder 15" dia., bears N.52°W., 54 lks. dist. mkd. ¼ S BT.

O.F. Thiel - For: Chaney - Nov. 14, 1913 (recorded 8/1998) - F.B. 115 Pg 96

Stone corner marked W.Oak 30" S.11°E., 1.27.
B.Oak bearing tree gone.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16814)

Point for the ¼ sec. cor. of secs. 10 and 11, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.
(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post 28" long, 2½" dia., 26" in the ground,
with broken clear glass at base, with brass cap mkd:

T 30 S R 4 W
1/4
S 10*S 11
1981

from which

An Oak 15" dia., bears S.85½°E., 128½ lks. dist. mkd. ¼
S11 BT.

A Fir 7" dia., bears S.58½°W., 79½ lks. dist. mkd. ¼ S10
BT.

From this point, an iron pipe, ¾" dia., firmly set, the
top 3" below surface of the ground, bears S.58°54'E., 0.865
chs. dist. This pipe is located 0.10 chs. W. of a corner
of wire fences, extending N.45°E. S., E., and W.

Fd. BC by R. Quimby, 3/2013 - M157-70