

PRIMARY CORNER DESCRIPTION Sec Cor for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6996-97)

-
- Set post cor. of secs. 2, 3, 10 and 11, from which
- A W.oak 12" dia., bears N.85°W., 142 lks. dist.
 - A B.Oak 6" dia., bears S.84°W., 166 lks. dist.
 - A W.oak 20" dia., bears S.33°E., 380 lks. dist.
 - A W.Oak 14" dia., bears N.27°E., 186 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page 7050-51)

Post to this cor., falling in a grain field, is gone, but the W.Oak 30" dia., mkd. S11 BT, is standing. None of the other bearing trees or their stumps are remaining. I restore this cor. by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, marked T30S S2 on NE.; R4W S11 on SE.; S10 on SW.; S3 on NW. faces, with 5 notches on S., and 2 notches on E. edges, from which

- A W.Oak 30" dia., bears S.33°E., 380 lks. dist. mkd. T30S R4W S11 BT. (This is the old bearing tree, which I remark, the old marks being dim.)
- A W.Oak 6" dia., bears S.50¼°W., 222 lks. dist. mkd. T30S R4W S10 BT.
- A Fir 24" dia., bears N.52°W., 202 lks. dist. mkd. T30S R4W S3 BT.

Wood's house bears S.22°W. No tree in Sec. 2.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16814-15)

The cor. of secs. 2, 3, 10 and 11, determined at record bearing and distance from the remains of a bearing tree mkd. by Thiel:

- A sawed Fir stump 45" dia., bears N.52°W., 202 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 42" in the ground, the top 14" below surface, with brass cap mkd: T 30 S R 4 W

S 3*S 2
S 10*S 11
1981

from which reference monuments:

- An iron post 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.25¼°E., 327½ lks. dist., with brass cap mkd. T30S R4W S11 RM 1981 and an arrow pointing to the corner. (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

An iron post 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.78 3/4°W., 92½ lks. dist., with brass cap mkd. T30S R4W S10 RM 1981 and an arrow pointing to the corner.

An iron post, 28" long, 2½" dia., 24" in the ground, for a reference monument, bears N.57¼°W., 114 lks. dist., with brass cap mkd. T30S R4W S3 RM 1981 and an arrow pointing to the corner.

Corner is located in cultivated field.

Fd. BC & Accessories per renewal notes, 3/2013 - R. Quimby, M157-70