

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6997)

Set ¼ sec. post at proper distance, from which
A B.Oak 10" dia., bears N.38°E., 120 lks. dist.
A W.Oak 12" dia., bears S.27°W., 180 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7054)

Set a Laurel post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W. face, from which
A W.Oak 24" dia., bears S.27°E., 120 lks. dist. mkd. ¼ S BT.
A B.Oak 20" dia., bears S.62°W., 172 lks. dist. mkd. ¼ S BT.
The W.Oak in Sec. 2 is plainly marked ¼ S BT, but the B.Oak in Sec. 2 has been chopped into and any marks thereon have been destroyed. I re-mark both bearing trees.

F.C. Frear, Deputy Co. Surveyor - Wit: A. Wallenburg; R. Morrison - Oct/Nov. 1918 - M 1-3; C.S. 7/18; Vol. 3 Pg. 29

Renew from old govt. trees. Set in 1" x 40" Iron pipe, from which
The old government trees remarked.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn; C.V. Story
C.S. File 40/273-1 - ~~Dec. 1949~~ 8/30/1950

A B.O. 25" dia., bears S.25°E., 79.5'.
At corner point found 1" iron pipe and fence post which I marked ¼ S, from which
A Cedar 14" dia., bears S.81°E., 24.5 ft mkd. ¼ S2 2880 BT
NE cor barn bears S.50°W., 116.0'
Center of Woods Creek RD bears West 438.0'
There are fences running N-E-W from this corner.
Information in italics add 8/14/2024 JC DCSO

Survey by R.M. Thompson - Dec. 17, 1955 - C.S. File 42/171

Found 1" iron pipe and 14" Cedar BT, S.81°E., 24.5 ft.
Marked new BT:
14" I.Cedar S.4°10'E., 29.3 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16815-16)

The ¼ sec. cor., perpetuated and recorded by Frear, in 1919, from original evidence no longer in existence, further perpetuated and recorded by Markham in 1949, and still further perpetuated and recorded by Thompson in 1955, monumented with an iron pipe, 1" dia., firmly set, the top 1" below surface of the ground, from which a bearing tree mkd. by Markham:

A Cedar 25" dia., bears S.78½°E., 38 lks. dist., with healed double blaze.

and a bearing tree mkd. by Thompson:

A Cedar 23" dia., bears S.2½°E., 46 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 28" in the ground, flush with surface, with brass cap mkd:

T 30 S R 4 W
1/4
S 3 | S 2
1981

from which a new bearing tree

A Cedar 7" dia., bears S.1 3/4°W., 110 lks. dist., mkd. ¼ S3 BT.

Reset iron pipe alongside iron post.

Fd Ok by Ron Quimby, March 1996 - M 123-58
Found OK by N. Hibbs, May 2003 - M137-63

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23519)

The ¼ sec. cor. of secs. 2 & 3, monumented with an iron post, 2½" dia., firmly set, flush with surface of the ground, with brass cap (properly) mkd.

from which the remains of a BT mkd. by Markham, Jr., in 1949, reported by Jelley in 1981-82

A sawed cedar stump, 28" dia., bears S.78½°E., 25.1 ft., with a healed blaze.

and a BT mkd. by Thompson, in 1955, reported by Jelley

A cedar, 31" dia., bears S.2½°E., 30.4 ft., with a healed blaze.

and a new bearing tree

A cedar, 11" dia., bears N.76¾°E., 62.8 ft., mkd. ¼ S2 BT.